

County Surveyor's Record, Douglas County, Oregon

14588

Dependent Resurvey, Portion of W. Bdy., T. 29 S., R. 1 W.

CHAINS

from which original bearing tree mkd. by F. Mensch

A fir, 23 ins. diam., bears N. 28° E., 102 lks. dist.,
mkd with scribe marks $\frac{1}{4}$ S31 BT visible on
open blaze.

and bearing tree mkd. by E. F. Strickler

A fir, 29 ins. diam., bears East, 73 lks. dist., with
scribe marks $\frac{1}{4}$ S31 BT visible on open blaze.


and bearing trees mkd. by J. M. Powell

A fir, 6 ins. diam., bears N. 22° E., 10.5 lks. dist.,
with scribe marks $\frac{1}{4}$ S31 BT visible on pitch covered
blaze.

A fir, 8 ins. diam., bears S. 39° E., 6 lks. dist.,
with scribe marks $\frac{1}{4}$ S31 BT visible on pitch
covered blaze.

N 1° 22' E., bet. secs. 31 and 36, beginning new measurement.

0.36 The $\frac{1}{4}$ sec. cor. of sec. 36 only, monumented with an iron post,
1 in. diam., firmly set, extending 16 ins. above the ground,
with brass cap mkd.



from which original bearing trees

A fir, 18 ins. diam., bears N. 24 $\frac{1}{2}$ ° W., 79 lks. dist.,
mkd. with healed blaze.

A decayed pine stump, 48 ins. diam., bears S. 88 $\frac{1}{2}$ ° W.,
61 lks. dist., no marks remain.

and bearing tree mkd. by J. M. Powell in 1969


A fir, 7 ins. diam., bears S. 74° W., 11 lks. dist.,
with scribe marks CS visible on pitched over blaze.

Descend 98 ft. over NW. slope.

7.80 Saddle, bears N, and W. 60° E.; asc. 173 ft. over SW. slope.

20.06 Point for the N 1/16 sec. cor. of sec. 31 only.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the
ground, with brass cap mkd.



from which

A fir, 9 ins. diam., bears N. 21° E., 11 lks. dist.,
mkd. X BT.

A fir, 10 ins. diam., bears S. 78° E., 12 lks. dist.,
mkd. N. 1/16 S31 BT.