

Dependent Resurvey, Portion of Subdivisional Lines, T. 27:S., R. 2 W.

CHAINS

A madrone, 16 ins. diam., bears S. 83° E., 30 lks. dist., with illegible scribe marks visible on opened blaze.

and trees marked by Corbin in 1957

A white pine, 10 ins. diam., bears N. 36° E., 19 lks. dist., with healed blaze.

A madrone, 16 ins. diam., bears N. 52° W., 67 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap marked

$$\frac{1}{4} S 4}{T 27 S R 2 W}$$
 1971

S. 89° 29' W., along the south bdy. of sec. 4, marking and blazing the true line.

Descend 140 ft. over SW. slope, across logged area, through scattering timber and light undergrowth.

- 5.85 Creek, 2 lks. wide, course S. 10° E.; asc. 205 ft. over SE. slope.
 - 17.30 Spur, slopes S. 10° W.; desc. 360 ft. over SW. slope.
 - 25.95 Little Creek, 2 lks wide, course S. 10° E.; asc. 255 ft. over E. slope.
 - 36.05 Spur, slopes S. 10° W.; desc. 115 ft. over SW. slope.
 - 38.95 Creek, 2 lks. wide, course S.; asc. 2 ft. over E. slope.
 - 38.98 True point for the closing cor. of secs. 8 and 9, on the S. bdy. of sec. 4, hereinafter described.
- Ascend 40 ft. over SE. slope.
- 40.03 The cor. of secs. 4 and 5 only, perpetuated by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 in. diam., firmly set, protruding 12 ins. above ground, with brass cap marked

$$\begin{array}{c} T 27 S \\ | \\ S 5 S 4 \\ \hline R 2 W \\ 1968 \end{array}$$

from which the original bearing trees

A fir, 35 ins. diam., bears N. 45° E., 30 lks. dist., no marks visible on weathered bark blaze.

A root hole, bears S. 30° E., 21 lks. dist., with a down and decayed fir alongside, size indeterminate, no marks visible.

A fir, 40 ins. diam., bears N. 80° W., 20 lks. dist., with scribe marks BT visible on weathered bark blaze.