

Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., E. 2 W.

CHAINS

A fir, 17 ins. diam., bears N. 69° E., 39 lks. dist.,
marked S 1/16 S9 BT.

A fir, 13 ins. diam., bears S. 79° W., 27 lks.
dist., marked S 1/16 S8 BT.

Descend 185 ft. over NE. slope, through scattering timber
and light undergrowth.

26.20 Little River, 1 ch. wide, course S. 55° W.; asc. 20 ft. over
SE. slope.

28.25 Little River Road, 50 lks. wide, bears N. 45° E. and S. 45° W.

40.28 The 1/4 sec. cor. of secs. 8 and 9, perpetuated by Vernon R. Tracy
Deputy County Surveyor, in 1957, monumented with an iron post, 1 in.
diam., firmly set, protruding 6 ins. above ground, with brass cap
marked

T27S
|
1/4 S 8 | S 9
R2W
1957

from which the remaining original bearing tree

A fir, 30 ins. diam., bears N. 66° W., 35 lks. dist.,
with healed blaze.

and a tree marked by Tracy, in 1957

A cedar, 13 ins. diam., bears S. 58° W., 67 lks.
dist., with healed blaze.

No other suitable trees available within limits.

The corner point is located in N.-S fence line.

N. 0° 15' W., beginning new measurement.

Ascend 195 ft. over S. slope, through scattering timber and
dense undergrowth.

18.15 Spur, slopes E.; desc. 50 ft. over NE. slope.

19.90 Creek, 2 lks. wide, course S. 40° E.; ascend 275 ft. over
SW. slope.

37.85 Spur, slopes N. 75° W.; desc, 5 ft. over NW. slope.

39.45 Creek, 1 lk. wide, course S. 40° W.; asc. 2 ft. over nearly
level ground.

39.64 Intersect the S. bdy. of sec. 4.

True point for closing cor. of secs. 8 and 9.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the
ground, with brass cap marked

S 4
S 8 | S 9
T 27 S | R 2 W
CC
1971

from which