

# County Surveyor's Record, Douglas County, Oregon

14553


Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., R. 2 W.

CHAINS

A fir, 25 ins. diam., bears S. 27° E., 52 lks. dist., marked T27S R2W S9 CC BT.

A maple, 12 ins. diam., bears S. 3° W., 80 lks. dist., marked T27S R2W S8 CC BT.

From this point the original closing cor. of secs. 8 and 9, bears N. 0° 15' W., 0.02 chs. dist., perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 in. diam., firmly set, protruding 7 ins. above ground, with brass cap marked



from which the original bearing trees

A decayed alder stump, size indeterminate, bears S. 60° E., 26 lks. dist., no marks visible.

A maple, 17 ins. diam., bears S. 23° W., 70 lks. dist., with scribe marks BT visible on opened blaze.

and trees marked by Tracy, in 1968

A fir, 25 ins. diam., bears S. 61° E., 69 lks. dist., with healed double blaze.

A yaw, 12 ins. diam., bears S. 47° W., 76 lks. dist., with scribe marks T27S R2W S8 CC BT visible on partially healed blaze.

From this same point, the cor. of secs. 4 and 5 only, bears S. 89° 29' W., 1.05 chs. dist., hereinbefore described.

Land, mountainous.  
 Soil, rocky clay loam.  
 Timber; fir, cedar, hemlock, maple, madrone, and alder; undergrowth, vine maple, salal, fern, hazel and poison oak.

From the cor. of sec. 8 and 9 only, on the N. bdy. of sec. 17.  
 S. 89° 26' W., along the S. bdy. of sec. 8.

Ascend 250 ft. over E. slope, through heavy timber and dense undergrowth.

- 5.00 Spur, slopes N. 20° E.; desc. 685 ft. over NW. slope.
- 35.85 Ravine, drains N. 40° E.; asc. 55 ft. over NE. slope.
- 40.05 The  $\frac{1}{4}$  sec. cor. of sec. 8 only, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1969, monumented with an iron post, 1 in. diam., firmly set, protruding 18 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked

