

Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., R. 2 W.

CHAINS

Alongside of which is the original basalt stone, 24 x 18 x 10 ins., marked  $\frac{1}{4}$  on N. face.

from which the original bearing trees

A fir, 30 ins. diam., bears N.  $19\frac{1}{2}^{\circ}$  E., 99 lks. dist., with burned and opened blaze.

A fir, 41 ins. diam., bears S.  $35\frac{1}{2}^{\circ}$  W., 79 lks. dist., with healed blaze.

and trees marked by Powell, in 1969

A pine, 8 ins. diam., bears N.  $44^{\circ}$  E., 74 lks. dist., with scribe marks  $\frac{1}{4}$  S8 BT visible on partially healed blaze.

A fir, 8 ins. diam., bears N.  $7^{\circ}$  W., 64 lks. dist., with healed double blaze.


S.  $89^{\circ} 41' W.$ , beginning new measurement

Ascend 40 ft. over NE. slope.

7.55 Spur, slopes N.; desc. 185 ft. over NW. slope.

28.30 Creek, 4 lks. wide, course N.; asc. 145 ft. over E. slope.

35.90 From this point, the original closing cor. of secs. 17 and 18, bears N., 10 lks. dist., perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1969, monumented with an iron post, 1 in. diam., protruding 8 ins. above ground, with brass cap marked



from which the original bearing trees

A root hole, bears S.  $19\frac{1}{2}^{\circ}$  E., 42 lks. dist., with a down fir alongside, 10 ins. diam., no marks visible.

A root hole, bears S.  $61^{\circ} 50' W.$ , 12 lks. dist., with a down fir alongside, 20 ins. diam., with illegible scribe marks visible on opened blaze.

and trees marked by Powell, in 1969

A fir, 35 ins. diam., bears S.  $35^{\circ}$  E., 29 lks. dist., with healed blaze.

A cedar, 27 ins. diam., bears S.  $2^{\circ}$  W., 47 lks. dist., with healed blaze.

A cedar, 10 ins. diam., bears N.  $28^{\circ}$  W., 11 lks. dist., with healed blaze.

40.77 The cor. of secs. 7 and 8 only, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1969, monumented with an iron post, 1 in. diam., firmly set,