


County Surveyor's Record, Douglas County, Oregon

14585

Dependent Resurvey, Portion of Subdivisional Lines T. 27 S., R. 2 W.

CHAINS

protruding 13 ins. above ground, with brass cap marked



BOOK
 O. B. B. B. B.
 9-1968
 M130-47

alongside of which is the original basalt stone, 14 x 10 x 7 ins. loosely set 2 ins. in the ground, marked with 4 notches on S. and 5 notches on E. edge.

from which the remaining original bearing trees

A fir, 50 ins. diam., bears N. 47½° E., 50 lks. dist., with axe marks visible on weathered bark blaze; remarked by Powell in 1969, with healed blaze.

A root hole, bears S. 47° E., 43 lks. dist., with a down fir alongside, 30 ins. diam., with healed blaze.

A fir stump, 18 ins. diam., bears N. 14° W., 122 lks. dist., with illegible scribe marks visible on opened blaze.

and trees marked by Powell, in 1969

A fir, 35 ins. diam., bears S. 22° E., 26 lks. dist., with healed double blaze.

A hemlock, 16 ins. diam., bears N. 45° W., 36 lks. dist., with scribe marks T27S R2W S7 CS ET visible on partially healed double blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber; fir, hemlock, cedar, maple, alder, madrone, and chinquapin; undergrowth, vine maple, salal, hazel, ceanothus, fern, and poison oak.


N. 0° 16' W., bet. secs. 7 and 8.

Descend 260 ft. over NE. slope, through heavy timber and dense undergrowth.

20.20 Little River, 50 lks. wide, course S. 80° W.; asc. 260 ft. over SE. slope.

21.85 Little River Road, 50 lks. wide, bears N. 85° W. and S. 85° E.

40.39 The ¼ sec. cor. of secs. 7 and 8, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 in. diam., firmly set, protruding 5 ins. above ground, with brass cap marked



alongside of which is the original basalt stone, 14 x 10 x 10 ins. loosely set, 2 ins. in the ground, marked ¼ on W. face.