

Dependent Resurvey, Portion of Subdivisional Lines, T. 27 S., R. 2 W.

CHAINS

from which the original bearing trees

A fir stump, 36 ins. diam., bears N. 88° E., 96 lks. dist., with scribe marks $\frac{1}{4}$ S8 BT visible on opened blaze.

A fir, 33 ins. diam., bears N. 20° W., 67 lks. dist., with healed blaze.

and trees marked by Tracy, in 1968

A fir, 10 ins. diam., bears S. 75° E., 23 lks. dist., with healed double blaze.

A pine, 17 ins. diam., bears S. 75° W., 26 lks. dist., with healed double blaze.

North, beginning new measurement.

Ascend 60 ft. over SE. slope, through heavy timber and dense undergrowth.

5.00 Spur, slopes N. 85° E.; desc. 55 ft. over NE. slope.

10.75 Ravine, drains S. 40° E.; asc. 700 ft. over S. slope.

40.29 The cor. of secs. 5, 6, 7, and 8, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an + marked on sandstone outcrop, 48 x 24 x 24 ins. above ground, from which the original bearing trees

A fir, 25 ins. diam., bears N. 84° E., 141 lks. dist., with scribe marks BT visible on opened blaze.

A fir, 54 ins. diam., bears S. 65° E., 137 lks. dist., with healed blaze.

A fir, 38 ins. diam., bears S. 23 $\frac{1}{2}$ ° W., 154 lks. dist., with scribe marks S7 BT visible on opened blaze.

A fir, 25 ins. diam., bears N. 31° W., 107 lks. dist., with illegible scribe marks visible on opened blaze.

and trees marked by Tracy in 1968

A fir, 11 ins. diam., bears N. 50° E., 12 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears S. 2° E., 36 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears S. 78° W., 14 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears N. 60° W., 17 lks. dist., with healed blaze.

and a reference monument by Tracy

An iron post, 1 in. diam., firmly set, protruding 13 ins. above ground, and in amount of stone, 3 ft. base, to top, bears west, 1.5 lks. dist., with brass cap marked T27S R2W S5 S6 S7 S8 1968.