

Dependent Resurvey, Portion of subdivisional Lines, T. 27 S., R. 2 W.

CHAINS	
0.37	<p>To complete the survey of sec. 8, I return to the $\frac{1}{4}$ sec. cor. of sec. 5 only, and run</p> <p>S. 89° 49' E., on the N. bdy. of sec. 8.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of sec. 8 only, at midpoint longitudinally on the N. bdy. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, in amount of stone, 2 ft. base, to top, with brass cap marked</p> <div style="text-align: center;"> $\frac{1}{4} S 8$ $T27S R2W$ 1971 </div> <p>from which</p> <p style="padding-left: 40px;">A maple, 3 ins. diam., bears S. 33° E., 17 lks. dist., marked X BT.</p> <p>No other suitable tree available within limits.</p>
<p>Subdivision of Section 8, T. 27 S., R. 2 W. Willamette Meridian, Oregon</p>	
20.22	<p>From the $\frac{1}{4}$ sec. cor. of sec. 8 only, on the S. bdy. of sec. 8.</p> <p>N. 0° 26' W., on the N. and S. center line of sec. 8, marking and blazing the true line.</p> <p>Descend 170 ft. over NE. slope, through heavy timber and dense undergrowth.</p> <p>Point for the center S 1/16 sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> $\begin{array}{c} C \\ \\ S \ 1/16 \ S \ 8 \\ \\ C \\ 1971 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 41° E., 26 lks. dist., marked CS 1/16 S8 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 82° W., 41 lks. dist., marked CS 1/16 S8 BT.</p> <p>Descend 95 ft. over NE. slope.</p>
28.10	<p>Little River, 50 lks. wide, course S. 75° W.; asc. 110 ft. over SW. slope.</p>
29.60	<p>Little River Road, 50 lks. wide, bears S. 60° E., and W.</p>
40.44	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 8, at intersection with the E. and W. center line.</p>

FD 11/90
M 111-6

FDOK
9-1998
D. Edwards
M 130-47

FD 11/90
M 111-6