

# County Surveyor's Record, Douglas County, Oregon

14589

## Subdivision of Section 8, T. 27 S., R. 2 W

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

C ¼ S 8  
T27S R2W  
1971

FROM  
7 1997  
C-151615  
M120-A7

from which

A fir, 6 ins. diam., bears S. 83° E., 48 lks. dist., marked C ¼ S 8 BT.

A pine, 15 ins. diam., bears N. 81° W., 14 lks. dist., marked C ¼ S 8 BT.

Ascend 135 ft. over SW. slope.

56.75 Spur, slopes N. 80° W.; desc. 30 ft. over NW. slope.

61.70 Dry creek, 2 lks wide, drains S. 70° W.; asc. 80 ft. over SW. slope.

66.60 Spur, slopes W.; desc. 65 ft. over NW. slope.

68.45 Creek, 3 lks. wide, course S. 10° W.; asc. 195 ft. over SW. slope.

80.44 The ¼ sec. cor. of sec. 8 only, on the N. bdy. of sec. 8.

From the ¼ sec. cor. of secs. 8 and 9.

S. 89° 39' W., on the E. and W. center line of sec. 8.

Ascend 220 ft. over SE. slope, through heavy timber and dense undergrowth.

27.95 Spur, slopes S. 5° W.; desc. 160 ft. over SW. slope.

40.17 The center ¼ sec. cor. of sec. 8.

Descend 15 ft. over SW. slope.

43.00 Greenman Creek, 3 lks. wide, course S. 45° E.; asc. 305 ft. over SE. slope.

80.81 The ¼ sec. cor. of secs. 7 and 8.

From the S 1/16 sec. cor. of secs. 8 and 9.

S. 89° 35' W., on the E. and W. center line of the SE ¼ of sec. 8.

Descend 170 ft. over NW. slope, through heavy timber and dense undergrowth.

8.80 Little River, 1 ch. wide, course S. 55° W.; asc. 50 ft. over NE. slope.

21.69 From this point, the NE. cor. of a wood frame buildings, bears S. 50 lks. dist., dimensions 24 x 24 ft., sides bear S. and W.

25.95 From this point, the SE. cor. of a wood frame shed bears S., 20 lks. dist., dimensions 10 x 26 ft., long side bears N.