

Dependent Resurvey, Portion of E. Bdy., T. 23 S., R. 10 W.

CHAINS

No other suitable trees available within limits.

N. 0° 35' W., bet. secs. 13 and 18, marking and blazing the true line.

Descend slightly across Ash Valley, along barbed wire fence, through thickets of blackberry vines.

23.50 Soup Creek, 5 lks. wide, course S. 60° W.; continue across Ash Valley.

35.35 Leave Ash Valley, enter heavy timber and dense undergrowth; also end of barbed wire fence; asc. 120 ft. over S. slope.

36.10 Dirt road, 15 lks. wide, bears N. 80° W. and S. 80° E.

39.00 Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

T 23 S  
R 10 W R 9 W  
¼  
S 13 | S 18  
1967

from which

A fir, 22 ins. diam., bears N. 38° E., 66 lks. dist., mkd. ¼ S18 BT.

A hemlock, 28 ins. diam., bears N. 38° W., 55 lks. dist., mkd. ¼ S13 BT.

From this point an unrecorded iron pipe, 1 in. diam., firmly set, protruding 8 ins. above ground, bears N. 11° 30' W., 0.62 chs. dist.

From this same point, a locally established corner monumented with a wooden hub, 2 x 2 ins., firmly set, protruding 2 ins. above ground, bears S. 88° 45' W., 0.74 chs. dist.,; from which

A fir, 43 ins. diam., bears N. 40° W., 32 lks. dist., mkd. ¼ S BT on opened blaze. (Annual ring count indicates the blaze to be about 50 years old.)

Ascend 250 ft. over S. slope.

48.10 Top of rock bluff, 50 ft. high, bears E. and W.; asc. 400 ft. over S. slope.

57.90 Ridge, bears E. and W.; desc. 295 ft. over NE. slope.

71.25 Creek, 2 lks. wide, course N. 40° W.; asc. 60 ft. over SW. slope.

78.00 The cor. of secs. 7, 12, 13, and 18, marked with the stump hole of the original corner tree from which the remains of original bearing trees:

A sawed fir stump, 48 ins. diam., bears N. 15° E., 42 lks. dist., with fragmentary scribe marks visible on bark blaze. (Record, N. 20° E.)