

# 14606 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 10 W.

CHAINS

An alder, 6 ins. diam., bears N. 80° E.,  
20 lks. dist., mkd. T23S R10W S13 BT on  
bark blaze.

A hemlock, 20 ins. diam., bears S. 39° E., 47 lks.  
dist., mkd. T23S R10W S24 BT.

A cedar, 30 ins. diam., bears S. 1° W., 39 lks. dist.,  
mkd. T23S R10W. S23 BT.

A hemlock, 20 ins. diam., bears N. 29° W., 45 lks. dist.,  
mkd. T23S R10W. S14 BT.

Land, east half mile, bottom land in Ash Valley, west half  
mile, mountainous.  
Soil, loam, rocky clay.  
Timber, fir, hemlock, cedar, maple, alder, myrtle and dogwood;  
undergrowth, blackberry, salmonberry, hazel, arrowwood, vine  
maple, vines and ferns.

N. 1° 19' W., bet. secs. 13 and 14.

Descend 15 ft. over NE. slope, across logged area, through  
dense undergrowth.

2.50 Spur, slopes NE.; desc. 45 ft. over NW. slope.

7.30 Spur, slopes N. 30° W.; desc. 390 ft. over NE. slope.

17.15 Dirt road, 15 lks. wide, bears E. and W.

19.50 Creek, 7 lks. wide, course E.; asc. 170 ft. over S. slope.

30.85 Ravine, drains S. 70° E.; asc. 80 ft. over S. slope.

35.10 Spur, slopes SE.; desc. 50 ft. over NE. slope.

39.50 The ¼ sec. cor. of secs. 13 and 14, reestablished during  
the survey of Elliott State Forest, in 1933. Subsequently,  
remonumented by James W. Byron, Deputy County Surveyor, in 1958  
with an iron post, 1½ ins. diam., firmly set, protruding 2 ins.  
above the ground, with brass cap mkd.

T 23 S R 10 W  
¼  
S 14 | S 13  
1958

*FDOK  
R. Ward  
12/97  
M12B-25*

from which the bearing tree marked in 1933

A hemlock, 34 ins. diam., bears S. 65° E., 33 lks. dist.,  
with scribe marks ¼ S visible on partially healed blaze.

and a tree marked by Byron

A hemlock, 14 ins. diam., bears N. 26½° W., 31 lks.  
dist., with a healed blaze.

N. 1° 00' W., beginning new measurement.

Descend 55 ft. over NE. slope.

2.60 Ravine, drains N. 40° E.; asc. 20 ft. over SE. slope.