

Dependent Resurvey, Portion of Subdivisional Lines, T. 23 S., R. 10 W.

CHAINS

- 5.10 Spur, slopes NE.; desc. 95 ft. over N. slope.
- 11.30 Creek, 1 lk. wide, course E.; asc. 155 ft. over S. slope.
- 12.00 Barbed wire fence, bears E. and W.
- 12.45 Gravel road, 25 lks. wide, bears E. and W.
- 17.25 Barbed wire fence, bears N. 30° W. and S. 40° E.
- 24.45 Spur, slopes S. 60° E; desc. 40 ft. over NE. slope.
- 28.30 Creek, 1 lk. wide, course S. 30° E.; asc. 375 ft. over SE. slope.
- 39.30 The cor. of secs. 11, 12, 13 and 14, rehabilitated during the survey of Elliott State Forest in 1933. Subsequently, remonumented and recorded by James W. Byron, Deputy County Surveyor, in 1958, with an iron post, 1½ ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.

T 23 S
 S 11 | S 12
 S 14 | S 13
 R 10 W
 1958

from which the remaining original bearing trees:

A sawed fir stump, 40 ins. diam., bears S. 43° E.,
 56 lks. dist., with opened blaze. no marks
 visible.

and bearing trees marked in 1933

A fir, 48 ins. diam., bears N. 48° E., 9 lks. dist.,
 with a healed blaze.

A sawed fir stump, 48 ins. diam. bears S. 11° W.,
 65 lks. dist., with fragmentary scribe marks
 visible on opened blaze.

A fir, 42 ins. diam., bears N. 78° W., 33 lks. dist.,
 with a healed blaze.

and bearing trees by Byron in 1958

A maple, 17 ins. diam., bears S. 78° E., 17 lks. dist.,
 with a partially healed blaze.

A fir, 23 ins. diam., bears S. 44½° W., 111 lks. dist.,
 with a healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, maple, alder, chinquapin,
 yew and myrtle; undergrowth, blackberry, huckleberry,
 willow, hazel, arrowwood, vine maple, vines and ferns.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the
 Tp.

N. 89° 29' W., bet. secs. 12 and 13.

Descend 125 ft. over SW. slope.