

T. 29S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of township 29 south, range 6 west, Willamette Meridian, Oregon, pertaining to this resurvey, is as follows:

The township boundaries and a portion of the subdivisional lines were surveyed by Nathaniel Ford, in 1854, as shown on the official plat of survey, approved March 9, 1855. The boundaries of Donation Land Claims were surveyed by Josiah A. Burnett, in 1860, as shown on the official plat of survey approved June 30, 1863.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding, or crossing, public lands were blazed.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated July 7, 1971, under Group Number 750, Oregon.

The direction of the lines were determined by deflection angles turned from azimuths obtained by direct solar observations.

The geographic position of the southeast corner of section 15, as scaled from the Roseburg, Oregon, quadrangle map, published by the United States Geological Survey, in 1955, is as follows:

Latitude 43° 02.5' N. Longitude 123° 23.1' W.

The mean magnetic declination is 19° 45' E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 29 W., R. 6 W., Willamette Meridian, Oregon

(Restoring the 1854 survey by Nathaniel Ford)

Beginning at the cor. of secs. 14, 15, 22, and 23, perpetuated by F.C. Frear, Deputy County Surveyor, in 1919, further perpetuated by James W. Byron, County Surveyor, in 1962, monumented with an iron post, 1 1-2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap marked

COUNTY SURVEYORS OFFICE

T 29 S R 6 W
 S 15 | S 14
 S 22 | S 23
 1962

from which the only remaining original bearing tree

A white oak, 39 ins. diam., bears N. 24° E.,
 500 lks. dist., with healed blaze.

and bearing trees marked by Frear in 1919

A fir stump, 32 ins. diam., bears S. 29° E.,
 33 lks. dist., with fragmentary scribe marks