

Dependent Resurvey, Portion of Subdivional Lines, T. 29 S., R. 6 W.

CHAINS

A fir, 9 ins. diam., bears N. 29° W.,  
116 lks. dist., marked 1/4 S15 BT.

N. 0° 49' E., beginning new measurement.

Ascend 70 ft. over S. slope.

4.85 Spur, slopes S. 60° W.; desc. 225 ft. over N. slope.

14.00 Ravine, drains W.; asc. 25 ft. over SW. slope.

17.95 Spur, slopes S. 80° E.; desc. 5 ft. over NE. slope.

18.80 Ravine, drains S. 40° E.; asc. 315 ft. over SW. slope.

32.70 Spur, slopes S. 65° W.; desc. 10 ft. over NW. slope.

38.00 The cor. of secs. 10, 11, 14, and 15, perpetuated by F.C. Frear, Deputy County Surveyor, in 1919, when original corner evidence was existent, further perpetuated by James W. Byron, County Surveyor, in 1962, monumented with an iron pipe, 1 in. diam., firmly set, protruding 4 ins. above ground, from which bearing trees marked by Byron in 1962

A fir, 13 ins. diam., bears N. 8° E.,  
22 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears S. 23° E.,  
61 lks. dist., with healed blaze.

A madrone, 13 ins. diam., bears S. 57° W.,  
53 lks. dist., with scribe marks T29S R6W  
S15 CS BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked

T 29 S R 6 W			
S 10		S 11	
S 15		S 14	
1971			

from which a new bearing tree

A fir, 13 ins. diam., bears N. 63° W.,  
130 lks. dist., marked T29S R6W S10 BT.

Deposit iron pipe alongside the iron post.

Land, rolling hills.

Soil, rocky clay loam.

Timber, fir, cedar, oak, and madrone; undergrowth, salal, rhododendron, vine maple, and poison oak.

From the cor. of secs. 14, 15, 22, and 23.

N. 87° 01' W., bet. secs. 15 and 22.

Ascend 110 ft. over NE. slope, through scattering timber and light undergrowth.

6.80 Spur, slopes N.; desc. 165 ft. over NW. slope.

13.85 Dirt road, 10 lks. wide, bears N. 40° E. and S. 40° W.