

County Surveyor's Record, Douglas County, Oregon

1613

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 W., R. 6 W.

CHAINS

- 16.70 East Fork Willis Creek, 3 lks. wide, course N. 5° E.; asc. 250 ft. over SE. slope.
- 30.75 Spur, slopes S. 20° E.; desc. 45 ft. over SW. slope.
- 35.80 Ravine, drains S. 5° E.; asc. 100 ft. over SE. slope.
- 39.99 The 1/4 sec. cor. of secs. 15 and 22, perpetuated by A. Boyer, Deputy County Surveyor, in 1937, from original evidence no longer in existence, monumented with an iron pipe, 1/2 in. diam., firmly set, protruding 6 ins. above ground, from which bearing trees marked by Boyer
 - A fir snag, 26 ins. diam., bears N. 44° W., 27 lks. dist., with healed blaze.
 - A fir, 15 ins. diam., bears S. 4° E., 38 lks dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{r} 1/4 \quad \frac{S \ 15}{S \ 22} \\ T \ 29 \ S \ R \ 6 \ W \\ 1971 \end{array}$$

from which a new bearing tree

 - A fir, 26 ins. diam., bears N. 14° W., 86 lks. dist., marked 1/4 S15 BT.

Deposit iron pipe alongside the iron post.

Corner located on spur, slopes S. 20° E.

N. 88° 50' W., beginning new measurement.

Descend 30 ft. over SW. slope.

- 0.75 Ravine, drains S.; asc. 310 ft. over **SE.** slope.
- 13.80 Spur ridge, slopes N. 10° E.; desc. 470 ft. over NW. slope.
- 17.85 Enter heavy timber, edge bears N. and S.
- 37.99 The cor. of secs. 15, 16, 21, and 22, determined by Ben B. Irving, County Surveyor, in 1929, at the intersection of blazed lines extending N. and E. and has long been recognized as the corner by adjacent land owners. This point was perpetuated by James W. Byron, County Surveyor in 1962, monumented with an iron pipe, 1/2 in. diam., firmly set, protruding 6 ins. above ground, from which bearing trees marked by Irving in 1929
 - A white oak, 12 ins. diam., bears N. 67° E., 21 lks. dist., with healed blaze.
 - A fir, 22 ins. diam., bears S. 27° E., 64 lks. dist., with healed blaze.
 - A root hole, bears S. 19° W., 57 lks, dist. with a fir stump alongside, 20 ins. diam., with no marks visible.