

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 6 W.

CHAINS

A fir stump, 28 ins. diam., bears N. 10° W., 93 lks. dist., with scribe marks BT visible on decayed opened blaze.

and a bearing tree marked by Byron in 1962

A white oak, 8 ins. diam., bears N. 5° W., 17 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam, 24 ins. in the ground, with brass cap marked

T 29	S R 6	W
S 16		S 15
S 21		S 22
1971		

from which a new bearing tree

A white oak, 8 ins. diam., bears S. 75° W., 87 lks. dist., marked T29S R6W S21 BT.

Deposit the iron pipe alongside the iron post.

Land, rolling hills.
Soil, rocky clay loam.
Timber, fir, cedar, hemlock, madrone, and oak; undergrowth, salal, hazel, vine maple, and poison oak.

N. 1° 29' E., bet. secs. 15 and 16.

Ascend 195 ft. over S. slope, through scattering timber and light undergrowth.

14.90 Spur, slopes S. 85° W.; desc. 15 ft. over NW. slope.

19.05 Ravine, drains S. 65° W.; asc. 10 ft. over SW. slope.

19.35 Wire fence, bears E. and W.

19.56 The S 1/16 sec. cor. of secs. 15 and 16, established by V.M. McLind, Registered Land Surveyor, No. 934, in 1971; monumented with an iron rod, 1/2 in. diam., firmly set, protruding 5 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked

S 1/16
S 16 S 15
1971

from which

A madrone, 6 ins. diam., bears N. 3° E., 76 lks. dist., marked S 1/16 S15 BT.

No other suitable trees available within limits.

Deposit the iron rod alongside the iron post.

N. 1° 29' E., beginning new measurement.

Ascend 65 ft. over SW. slope.

2.80 Spur, slopes W.; desc. 345 ft over NW slope.