

County Surveyor's Record, Douglas County, Oregon

14615

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 W., R. 6 W.

CHAINS

- 17.56 Creek, 5 lks. wide, course NE.; asc. 10 ft. over SE. slope.

- 19.56 The 1/4 sec. cor. of secs. 15 and 16, reestablished by proportionate measurement by V.M. McLind, Registered Land Surveyor, No. 934, in 1971, monumented with an iron rod, 1/2 in. diam., firmly set, protruding 5 ins. above ground, from which a bearing tree marked by McLind:
 - A maple, 17 ins. diam., bears S. 88° E.,
76 lks. dist., with scribe marks T29S
R6W 1/4 S15 BT visible on open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap marked

	1/4	
S 16		S 15
T 29	S R 6	W
	1971	

from which a new bearing tree

 - A fir, 11 ins. diam., bears S. 5° W.,
42 lks. dist., marked 1/4 S16 BT.

Deposit the iron rod alongside the iron post.

Corner located on spur, slopes NE.

N. 1° 29' E., beginning new measurement.

Descend 195 ft. over NE. slope.

- 8.50 Intersect the S. bdy. of Donation Land Claim No. 41.

From this point the point for the SW. cor. of Donation Land Claim No. 41, bears N. 89° 43' W., 10.62 chs. dist.

- 11.90 Dirt road, 15 lks. wide, bears N. 35° W., and S. 35° E.

- 16.00 West Willis Creek Road, 20 lks. wide, bears N. 45° E. and S. 45° W.

- 17.40 Wire fence, bears NE. and SW.

- 20.10 West Willis Creek, 5 lks. wide, course N. 15° E.; asc. 40 ft. over nearly level land.

- 36.40 Wire fence, bears N. 20° E. and S. 20° W.

- 39.12 The cor. of secs. 9, 10, 15, and 16, reestablished by proportionate measurement by V.M. McLind, Registered Land Surveyor, No. 934, in 1971, monumented with an iron rod, 1/2 in. diam., firmly set, protruding 6 ins. above ground, from which bearing trees marked by McLind:
 - An alder, 13 ins. diam., bears N. 49° E.,
240 lks dist., with scribe marks T29S
R6W S10 BT visible on open double blaze.
 - A white oak, 24 ins. diam., bears S. 41° E.,
385 lks. dist., with scribe marks T29S R6W
S15 BT visible on open double blaze.
 - A white oak, 27 ins. diam., bears N. 73° W.,
240 lks. dist., with scribe marks T29S R6W
S9 BT visible on open double blaze.

At the corner point