

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 6 W.

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked

T 29 S R 6 W
 $\frac{S 9}{S 16} | \frac{S 10}{S 15}$
 1971

No suitable tree available within limits in sec. 16.

Deposit the iron rod alongside the iron post.

Land, rolling hills.
 Soil, rocky clay loam.
 Timber, fir, cedar, hemlock, madrone, and oak; undergrowth, salal, hazel, vine maple, and poison oak.

From the cor. of sec. 10, 11, 14, and 15.

N. 86° 43' W., bet. secs. 10 and 15.

Descend 375 ft. over W. slope, through scattering timber and dense undergrowth.

32.00 Creek, 4 lks. wide, course S. 20° W.; asc. 75 ft. over SE. Slope.

38.29 The 1/4 sec. cor. of secs. 10 and 15, perpetuated by James W. Byron, County Surveyor, in 1962, monumented with an iron pipe, 1/2 in. diam., firmly set, protruding 6 ins. above ground, from which the only remaining original bearing tree

A white oak, 27 ins. diam., bears S. 18° W., 70 lks. dist., with fragmentary scribe marks visible on opened blaze and scribe marks 1/4 S15 CS BT visible on partially healed blaze. (Remarked by Byron in 1962)

and a bearing tree marked by Byron in 1962

A white oak, 10 ins. diam., bears N. 22° W., 16 lks dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked

1/4 $\frac{S 10}{S 15}$
 T 29 S R 6 W
 1971

Deposit the iron pipe alongside the iron post.

Corner located on spur, slopes SW.

N. 87° 03' W., beginning new measurement

Descend 180 ft. over NW. slope.

12.05 Creek, 4 lks. wide, course S. 55° W.; asc. 45 ft. over SE. slope.

21.05 Spur, slopes S. 15° W.; desc. 130 ft. over W. slope.