

County Surveyor's Record, Douglas County, Oregon

14817

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 6 W.

CHAINS	
36.00	Willis Creek, 40 lks. wide, course N. 60° W.; asc. 40 ft. over E. slope.
36.55	Willis Creek Road, 30 lks. wide, bears N. 20° W. and S. 20° E.
38.20	Wire fence, bears N. 20° W. and S. 20° E.
39.43	The cor. of secs. 9, 10, 15, and 16. Land, rolling hills. Soil, rocky clay loam. Timber, fir, hemlock, cedar, madrone, and oak; undergrowth, salal, hazel, and poison oak.
	N. 3° 59' E., bet. secs. 9 and 10. Descend 40 ft. over nearly level land through scattering timber and light undergrowth.
2.20	Willis Creek Road, 20 lks. wide, in curve, bears N. 40° W. and S. 25° E.
39.21	The 1/4 sec. cor. of secs. 9 and 10, perpetuated and recorded by J.H. Markham, Registered Professional Engineer No. 2880, in 1953, from original evidence no longer in existence, monumented with an iron rod, 1 in. diam., firmly set, with top 6 ins. below surface of ground, from which a bearing tree marked by Markham in 1953 A maple, 25 ins. diam., bears N. 24° W., 253 lks. dist., with healed double blaze. At the corner point Set an iron post, 28 ins. long, 2 1/2 ins. diam., 36 ins. in the ground, with the top 8 ins. below surface of ground, with brass cap marked <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} 1/4 \\ S \ 9 \ \ S \ 10 \\ T \ 29 \ S \ \ R \ 6 \ W \\ 1971 \end{array}$ </div> from which a bearing object A power pole, B7900 #25, bears S. 29° E., 504 lks. dist.
	N. 2° 11' W., beginning new measurement. Ascend 165 ft. over SE. slope.
4.80	Willis Creek Road, 30 lks. wide, bears N. 35° E. and S. 35° W.
5.35	Wire fence, bears N. 35° E. and S. 35° W.
13.32	Intersect the N. bdy. of Donation Land Claim No. 41 Point for the closing corner of secs. 9 and 10. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked