

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 6 W.

CHAINS

C C
T 29 S R 6 W
S 9 | S 10
C 41
1971

from which

A black oak, 13 ins. diam., bears N. 61° E.,
38 lks. dist., marked T29S R6W S10 CC BT.

A fir, 15 ins. diam., bears N. 5° W., 23 lks.
dist., marked T29S R6W S9 CC BT.

From this point the exterior cor. on the N bdy. of
Claim No. 41, bears S. 89° 43' W., 6.96 chs. dist.,
hereinafter described.

Ascend 20 ft. over SE. slope.

- 16.20 Spur, slopes E.; desc. 25 ft. over NE. slope.
- 19.25 Ravine, drains S. 80° E.; asc. 85 ft. over SE. slope
- 24.50 Spur, slopes E.; desc. 55 ft. over NE. slope.
- 28.80 Ravine, drains S. 55° E.; asc. 30 ft. over SE. slope.
- 30.90 Spur, slopes S. 60° E.; desc. 80 ft. over NE. slope.
- 33.10 Dry creek, 3 lks. wide, course N. 80° E.; asc. 110 ft.
over SE. slope.
- 37.73 The cor. of secs. 3, 4, 9, and 10, perpetuated by G.G.
Steward, Deputy County Surveyor, in 1922, further per-
petuated by James W. Byron, County Surveyor, in 1954,
monumented with an iron pipe, 1/2 in. diam., firmly set,
protruding 5 ins. above ground, with brass cap marked

D

from which the remaining original bearing trees

A root hole, bears S. 81° E., 99 lks. dist.,
with a down and decayed black oak, size
indeterminate, alongside, with no marks
remaining.

A white oak, 36 ins. diam., bears N. 1° W.,
142 lks. dist., with healed blaze. (Record
bearing, N. 27° W.)

and a bearing tree marked by Stewart in 1922

A white oak, 16 ins. diam., bears N. 40° E.,
27 lks. dist., with healed blaze.

and bearing trees marked by Byron in 1954

A fir, 18 ins., diam., bears S. 71° E.,
46 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 74° W.,
29 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap marked

T 29 S R 6 W
S 4 | S 3
S 9 | S 10
1971