

County Surveyor's Record, Douglas County, Oregon

14822

Dependent Resurvey, Portion of Bdys., Claim No. 41, T. 29 W., R. 6 W.

CHAINS

N. 89° 43' E., along the N. bdy. of Claim No. 41.
 Descend 115 ft. over E. slope, through scattering timber and light undergrowth.

6.96 Intersect line bet. secs. 9 and 10.

Point for the closing cor. of the line bet. sec. 9 and 10 with the N. bdy. of Claim No. 41, hereinbefore described.

From this point the 1/4 sec. cor. of secs. 9 and 10, bears S. 2° 11' E., 13.32 chs. dist., hereinbefore described.

Descend 95 ft. over E. slope.

12.44 Willis Creek Road, 30 lks. wide, bears N. 30° E. and S. 30° W.

12.70 Wire fence, bears N. 30° E. and S. 30° W.

19.30 Willis Creek, 5 lks. wide, course N.; asc. 165 ft. over W. slope.

27.70 Spur, slopes S. 10° W.; desc. 5 ft. over E. slope.

30.10 Ravine, drains S. 30° E.; asc. 70 ft. over W. slope.

33.24 The NE. cor. of Claim No. 41, perpetuated and recorded by F.C. Frear, Deputy County Surveyor, in 1917, from original evidence no longer in existence, further perpetuated by James W. Byron, County Surveyor, in 1954, monumented with an iron bolt, 1/2 in. diam., firmly set, protruding 8 ins. above ground, from which bearing trees marked by Frear in 1917

A white oak, 10 ins. diam., bears N. 37° E., 13 lks. dist., with healed double blaze.

A white oak, 8 ins. diam., bears S. 17° W., 9 lks. dist., with scribe marks CS C41 BT visible on opened blaze.

and a bearing tree marked by Byron in 1954

A white oak, 10 ins. diam., bears S. 40° E., 5 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked

T 29 S R 6 W

C 41 S 10
 1971

Deposit iron bolt alongside the iron post.

Subdivision of Section 15, T. 29 S., R. 6 W.,
 Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 15 and 22.

N. 2° 34' E., on the N. and S. center line of sec. 15.