

Dependent Resurvey, Portion of Subdivisional Lines, T. 33 S., R. 5 W.

| CHAINS |   |
|--------|---|
| 30.55  | Spur, slopes NW.; desc. 275 ft. over NE. slope.   |
| 39.61  | The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 2-1/2 ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd. and witnessed as described in the official record of the 1965 remonumentation.   |
|        | N. 0° 11' E., beginning new measurement.  |
|        | Descend 435 ft. over NE. slope, across logged area.   |
| 14.50  | Mining ditch, 10 lks. wide, bears N. 55° W. and S. 55° E.   |
| 18.955 | An original line tree, a sawed Douglas fir stump, 28 ins. diam., mkd, with one blaze on S. and one Blaze on N. face, and with scribe marks MSS BT visible on bark blaze on NE. face   |
|        | N. 0° 33' E., beginning new measurement.  |
|        | Descend 60 ft. over NE. slope, across logged area.  |
| 1.885  | The N 1/16 sec. cor. of secs. 1 and 2, established and recorded by Ben B. Irving, Deputy County Surveyor, in 1930, monumented with an iron pipe, 1-1/4 ins. diam., firmly set, protruding 4 ins. above the ground, and in a mound of stone, 1 ft. base, to top, from which a bearing tree mkd. by Irving: |
|        | A yew, 14 ins. diam., bears S. 82° W., 16-1/2 lks. dist., with scribe marks N 1/16 S2 CS visible on open double blaze.  |
|        | At the corner point   |
|        | Set an iron post, 28 ins. long, 2-1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  |
|        | N 1/16<br>N 2/S 1<br>1970   |
|        | from which new bearing trees  |
|        | A cedar, 31 ins. diam., bears S. 11° E., 87 lks. dist., mkd. N 1/16 S1 BT.  |
|        | A Douglas fir, 10 ins. diam., bears S. 47° W., 60 lks. dist. mkd. N 1/16 S2 BT.   |
|        | Deposit the iron pipe alongside the iron post.  |
|        | N 0° 09' E., beginning new measurement.   |
|        | Descend 10 ft. over NE. slope, across logged area.  |
| 1.30   | Quines Creek, 25 lks. wide, course N. 70° W.; asc. 3 ft. over SW. slope.  |
| 1.655  | The NW. cor of Quartz Mill Mine, established and recorded by Ben B. Irving, Deputy County Surveyor, monumented with an iron pipe 1-1/4 ins. diam., firmly set, protruding 8 ins. above ground, and in a mound of stone, 2 ft. base, to top, form which bearing trees mkd. by Irving:                      |