

County Surveyor's Record, Douglas County, Oregon

1432

Subdivision of Section 1, T. 33 S., R. 5 W.

CHAINS	
	<p>Tp.</p> <p>N. 89° 49' W., on the E. and W. center line of sec. 1.</p> <p>Descend 85 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
6.75	Spur, slopes SW.; desc. 775 ft. over NW. slope.
40.60	Leave heavy timber, edge bears N. and S.; enter logged area covered with scattering timber and light undergrowth.
40.73	The center 1/4 sec. cor of sec. 1.
	Descend 260 ft. over NW. slope.
51.45	Dirt road, 15 lks. wide, bears N. 25° E. and S. 25° W.
53.00	Leave logged area, edge bears N. 25° E., and S. 25° W.; enter open pasture.
58.00	Leave open pasture, edge bears NE. and SW.; enter logged area.
62.28	Quines Creek, 20 lks. wide, course N W.; asc. 5 ft. over NE. slope.
62.80	Point for the center W. 1/16 sec. cor. of sec. 1.
	Set an iron post, 28 ins. long, 2-1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>W 1/16</p> <p>C S 1 C</p> <p>1970</p>
	from which
	<p>A Douglas fir, 15 ins. diam., bears N. 48° W., 63 lks. dist., mkd. CW 1/16 S1 BT.</p> <p>A Douglas fir, 15 ins. diam., bears S. 38° E., 37 lks. dist., mkd. CW 1/16 S1 BT.</p>
	Ascend 75 ft. over NE. slope.
67.10	Spur, slopes N.; desc. 25 ft. over NW. slope; also NE. cor of timber, continue slong S. edge of logged area.
68.75	Creek, 1 lk. wide, course N. 10° E.; asc. 265 ft. over NE. slope.
78.00	Spur, slopes N.; asc. 20 ft. along N. slope.
82.00	Ravine, drains N. 20° E.; asc. 50 ft. over NE. slope.
84.87	The 1/4 sec. cor. of secs. 1 and 2.
	From the W 1/16 sec. cor. of secs. 1 and 12.
	N. 0° 38' W., on the N. and S. center line of the SW1/4 of Sec. 1.
	Ascend 60 ft over SE. slope, through heavy timber and moderate undergrowth.
6.30	Spur, slopes N. 65° E.; desc. 45 ft. over NE. slope.