

Subdivision of Section 1, T. 33 S., R. 5 W.

CHAINS	
8.60	Ravine, drains E.; asc. 135 ft. over SE. slope.
15.65	Spur, slopes E.; desc. 130 ft. over NE. slope.
19.77	Point for the SW 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of the SW1/4.
	Set an iron post, 28 ins. long, 2-1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SW 1/16 S 1 1970
	from which
	A cedar, 11 ins. diam., bears N. 70° W., 74 lks. dist., mkd. SW 1/16 S1 BT.
	A Douglas fir, 22 ins. diam., bears S. 9° E., 15 lks. dist., mkd. SW 1/16 S1 BT.
	The cor. falls at the SW. cor of a logged area.
	Descend 195 ft. over NE. slope; through a logged area covered with scattering timber and moderate undergrowth.
29.05	Ravine, drains N. 65° E.; desc. 5 ft. along E. slope.
31.85	Spur, slopes E.; desc. 210 ft. over NE. slope.
39.54	The center W. 1/16 sec. cor. of sec. 1.
	From the center S 1/16 sec. cor. of sec. 1.
	N. 89° 53' W., on the E. and W. center line of the SW.1/4 of sec. 1.
	Descend 120 ft. over SW. slope, through heavy timber and moderate undergrowth, along S. edge of a logged area.
0.75	Dirt road, 15 lks. wide, bears NW. and SE.
4.80	Dirt road, 15 lks. wide, bears NW. and SE.
7.55	Irrigation ditch, 2 lks. wide, course N. 10° W.
7.95	Quines Creek, 15 lks. wide, course N. 35° W.; desc. 5 ft. over SW. slope.
9.55	Creek, 10 lks. wide, course N. 10° W.; asc 290 ft. over NE. slope.
22.23	The SW 1/16 sec. cor. of sec. 1.
	Ascend 375 ft. over broken NE. slope.
41.60	Spur ridge, bears N. 30° W. and S. 30° E.; desc. 60 ft. over NW. slope.
44.45	The S 1/16 sec. cor. of secs. 1 and 2.
	From the center W 1/16 sec. cor of sec. 1.
	N. 0° 29' W., on the N. and S. center line of NW1/4 sec. 1.
	Descend 10 ft. along the left bank of Quines Creek,