

14854 County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 1, T. 33 S., R. 5 W.

CHAINS

- through scattering timber and dense undergrowth; across logged area.
- 1.90 Channel of Quines Creek, 10 lks. wide, course NW.; desc. 5 ft. over nearly level ground.
- 3.00 Channel of Quines Creek, 15 lks. wide, course N. 80° W.; asc. 20 ft. over nearly level ground.
- 4.00 Top of ascent, slopes W.; desc. 25 ft. along W. slope.
- 6.90 Irrigation ditch, 2 lks. wide, course N. 30° W.
- 10.90 Dirt road, 15 lks. wide, bears N. 50° W. and S. 60° E. on curve.
- 11.70 Creek, 2 lks. wide, course N. 60° W.; asc 55 ft. over SW. slope.
- 13.30 Irrigation ditch, 1 lk. wide, course N. 70° W.
- 19.75 Dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.
- 20.775 Point for the NW 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of NW1/4.
- Set an iron post, 28 ins. long, 2-1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- NW 1/16 S 1
1970
- from which
- A Douglas fir, 12 ins. diam., bears N. 48° E., 40-1/2 lks. dist., mkd. NW 1/16 S1 BT.
- A cedar, 12 ins. diam., bears S. 20° E., 36-1/2 lks. dist., mkd. NW 1/16 S1 BT.
- Ascend 5 ft. over SW. slope.
- 21.45 Spur, slopes W.; desc. 40 ft. over NW. slope.
- 27.00 Dirt road, 15 lks. wide, bears NE. and S. 20° W. in a curve.
- 32.90 Dirt road, 15 lks. wide, bears N. 20° W. and S. 20° E.
- 35.10 Creek, 1 lk. wide, course S. 80° W.; asc. 135 ft. over SW. slope.
- 42.23 The W 1/16 sec. cor. of sec. 1 only, on the N. bdy. of the Tp., monumented with an iron post, 2-1/2 ins diam., protruding 8 ins. above ground, with brass cap mkd. and witnessed as described in the official record of 1965 dependent resurvey.
-
- From the center N 1/16 sec. cor. of sec. 1.
- N. 89° 40' W., on the E. and W. center line of the NW1/4 of sec. 1.
- Descend 325 ft. over SW. slope, through heavy timber and light undergrowth, along N. edge of logged area.
- 21.84 The NW 1/16 sec. cor. of sec. 1.