

# County Surveyor's Record, Douglas County, Oregon

14839

Dependent Resurvey, Portion of S. Bdy., T. 22 S., R. 10 W.

CHAINS

A fir, 29 ins. diam., bears S. 38° E., 28 lks. dist., with scribe mark S visible on partially open blaze. (Record, S. 25° E.)

A fir, 40 ins. diam., bears S. 88° W., 46 lks. dist., with scribe marks T23S R10W S2 BT visible on bark blaze. This tree was rescribed BT by Oregon State Board of Forestry, in 1957.

and a bearing tree mkd. by Oregon State Board of Forestry

A fir, 16 ins. diam., bears S. 44°W., 20 1/2 lks. dist., with healed blaze.

N. 89° 53' W., along the S. bdy. of sec. 35, marking and blazing the true line.

Ascend 120 ft. over NE. slope, through heavy timber and dense undergrowth.

7.825 The 1/4 sec. cor. of sec. 2 only, T. 23 S., R. 10 W., perpetuated and recorded by the Oregon State Board of Forestry in 1958, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

1/4 S 2  
1958

from which the original bearing trees:

A fir snag, 58 ins. diam., bears S. 80° W., 15 lks. dist., with scribe marks S2 1/4 T23S R10W visible on bark blaze.

A fir stump, 36 ins. diam., bears N. 75° W., 35 lks. dist., with healed blaze.

S. 89° 56' W., beginning new measurement.

Ascend 110 ft. over NE. slope, through heavy timber and dense undergrowth.

9.40 Creek, 5 lks. wide, course N. 45° E.; asc. 95 ft. over NE. slope.

11.50 Paved road, 30 lks. wide, bears N. 35° W., and S. 35° E.

15.30 Ravine, drains N. 40° E.; asc. 340 ft. over NE. slope.

23.60 Spur, slopes N. 30° E.; desc. 50 ft. over NW. slope.

26.65 Creek, 2 lks. wide, course N. 35° E.; asc. 195 ft. over NE. slope.

31.82 The 1/4 sec. cor. of sec. 35 only, perpetuated and recorded by the Oregon State Board of Forestry in 1958, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 4 ins. above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

1/4 S 35  
1958

from which the original bearing trees:

A fir stump, 28 ins. diam., bears S. 83° E., 21 lks. dist., with scribe marks 1/4 S visible on partially open blaze. (Record, N. 80° E.)