

County Surveyor's Record, Douglas County, Oregon

14840

Dependent Resurvey, Portion of S. Bdy., T. 22 S., R. 10 W.

CHAINS	
	<p>A root hole, bears S. 54° E., 13 lks. dist., with a down maple alongside, 32 ins. dia., no marks visible, (Record, S. 71° E.)</p> <p>and a bearing tree mkd. by the Oregon State Board of Forestry</p> <p>A fir, 40 ins. diam., bears N. 2 1/2° W., 101 lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p>A hemlock, 9 ins. diam., bears N. 38 1/4° E., 57 1/2 lks. dist., mkd. 1/4 S35 BT.</p> <p>A hemlock, 7 ins. diam., bears N. 67 1/2° E., 54 1/2 lks. dist., mkd. X.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 03' W., beginning new measurement.</p> <p>Ascend 3 ft. over NE. slope.</p>
1.335	<p>The closing corner of secs. 2 and 3, T. 23 S., R. 10 W., reestablished and recorded by the Oregon State Board of Forestry in 1958, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 22 S R 10 W</p> <p style="margin-left: 40px;">S 35</p> <hr style="width: 40%; margin: 0 auto;"/> <p style="margin-left: 40px;">S 3 S 2</p> <p>T 23 S R 10 W</p> <p style="margin-left: 40px;">CC</p> <p style="margin-left: 40px;">1958</p> </div> <p>from which new bearing trees</p> <p>A wild cherry, 5 ins. diam., bears S. 10 3/4° E., 14 1/2 lks. dist., mkd. T23S R10W S2 CC BT.</p> <p>An alder, 7 ins. diam., bears S. 33° W., 45 lks. dist., mkd. T23S R10W S3 CC BT on bark blaze.</p> <p>Ascend 100 ft. over NE. slope.</p>
7.90	<p>Spur, slopes N.; desc. 140 ft. over broken NW. slope.</p>
15.10	<p>Spur, slopes NE.; desc. 180 ft. over NW. slope.</p>
19.58	<p>Point for the W 1/16 sec. cor. of sec. 35 only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p><u>W 1/16 S 35</u></p> <p>1970</p> </div> <p>from which</p> <p>A maple, 20 ins. diam., bears N. 33 1/4° E., 49 lks. dist., mkd. W 1/16 S35 BT.</p> <p>Descend 65 ft. over NW. slope.</p>
21.00	<p>Ravine, drains N. 30° E.; asc. 570 ft. over NE. slope.</p>
39.16	<p>The cor. of secs. 34 and 35 only, monumented with the original sandstone boulder, 5 x 4 x 3 ft. high, mkd. X on top, from which the remaining original bearing trees:</p>