

Dependent Resurvey, Portion of S. Bdy., T. 22 S., R. 10 W.

CHAINS

A root hole, bears N. 80° E., 12 lks. dist., with a down fir alongside, 30 ins. diam., with healed blaze.

A root hole, bears S. 6° W., 15 lks. dist., with a down fir alongside, 52 ins. diam., with fragmentary scribe marks visible on partially open blaze.

and a tree of no record

A fir, 44 ins. diam., bears N. 6° E., 167 lks. dist., with fragmentary scribe marks visible on partially open blaze.

At the corner point

Seat a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in drill hole, in solid rock, with top mkd.

T 22 S R 10 W
 S 34 | S 35
 S 3

T 23 S R 10 W
 1970

from which a bearing object

A sandstone boulder, 25 x 20 x 20 ft. high, bears N. 31° W., 23 lks. dist., mkd. X B O on E. face.

There are no suitable bearing trees available within limits.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, oak, maple, and alder; undergrowth, salal, vine maple, poison oak, fern, rhododendron, and arrowwood.

Dependent Resurvey of a Portion of the East Boundary,
 T. 22 S., R. 10 W., Willamette Meridian, Oregon

(Restoring the 1874 survey, the 1878 survey and resurvey by William H. Byars, the 1894 retracement by Aurelius Todd, and the 1895 retracement by Alonzo Gesner)

From the cor. of secs. 25, 30, 31, and 36, determined at record bearing and distance from the remaining original bearing tree:

A fir, 22 ins. diam., bears S. 35° W., 40 lks. dist. with fragmentary scribe marks visible on open and burned blaze. (Record, estimated 40 lks.)

At the corner point

Seat a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in drill hole, in solid rock, with top mkd.

T 22 S
 R 10 W R 9 W
 S 25 | S 30
 S 36 | S 31
 1970

From which reference monuments and bearing objects

A brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, in solid rock, for a reference monument, bears N. 88 3/4° E., 7 lks. dist., with