

# County Surveyor's Record, Douglas County, Oregon

14842

Dependent Resurvey, Portion of E. Bdy. T. 22 S., R. 10 W.

CHAINS																
	<p>top mkd. T22S R9W S30 RM 1970 and an arrow pointing to the corner.</p> <p>A rock ledge, bears S. 2 1/2° E., 21 lks. dist., mkd. X B O.</p> <p>A brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in a drill hole, in solid rock, for a reference monument, bears S. 49 1/4°W., 7 lks. dist. with top mkd. T22S R10W S36 RM 1970 and an arrow pointing to the corner.</p> <p>Same rock ledge, bears N. 46°W., 23 1/2 lks. dist. mkd. X B O.</p> <p>The corner is located on the point of large rock outcrop. N. 1° 49' W., along E. bdy. of sec. 25, marking and blazing the true line.</p> <p>Ascend 150 ft. over S. slope, through scattering timber and dense undergrowth.</p>															
4.05	Spur ridge, bears N. 70°E. and S. 70° W.; desc. 145 ft. over NE. slope.															
7.90	Bottom of descent, slopes W.; asc. 495 ft. over SE. slope.															
36.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, determined by the method of irregular boundaries; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td></td><td style="text-align: center;">1/4</td><td></td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;"> </td><td style="text-align: center;">S 30</td></tr> <tr><td style="text-align: center;">R 10 W</td><td style="text-align: center;"> </td><td style="text-align: center;">R 9 W</td></tr> <tr><td style="text-align: center;">T 22 S</td><td></td><td></td></tr> <tr><td></td><td style="text-align: center;">1970</td><td></td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears N. 71°E., 22 1/2 lks. dist., mkd. 1/4 S30 BT.</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears S. 71°W., 15 1/2 lks. dist., mkd. 1/4 S25 BT.</p> <p>Set an iron pipe, 36 ins. long 3/4 in. diam., 24 ins. in ground alongside the iron post.</p>		1/4		S 25		S 30	R 10 W		R 9 W	T 22 S				1970	
	1/4															
S 25		S 30														
R 10 W		R 9 W														
T 22 S																
	1970															
	<hr style="width: 20%; margin: 0 auto;"/> <p>N. 1° 35' W., beginning new measurement.</p> <p>Ascend 20 ft. over SW. slope.</p>															
2.00	Top of ascent, slopes W.; desc. 145 ft. over broken NW. slope.															
16.00	Bottom of descent, slopes W.; asc. 410 ft. over broken S. slope.															
35.95	Spur ridge, bears N. 80° W. and S. 80° E.; desc. 215 ft. over N. slope.															
38.82	<p>Point for the cor. of secs. 19, 24, 25, and 30, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>															