

Dependent Resurvey, Portion of E. Bdy., T. 22 S., R. 10 W.

CHAINS

T 22 S	
R 10 W	R 9 W
S 24	S 19
S 25	S 30
1970	

from which

- A hemlock, 43 ins. diam., bears N. 62 1/2° E., 61 1/2 lks. dist., mkd. T22S R9W S19 BT.
- A hemlock, 45 ins. diam., bears S. 56° E., 50 lks. dist., mkd. T22S R9W S30 BT.
- A hemlock, 36 ins. diam., bears S. 78 1/4° W., 74 lks. dist., mkd. T22S R10W S25 BT.
- A hemlock, 19 ins. diam., bears N. 36° W., 68 lks. dist., mkd. T22S R10W S24 BT.

From this point the cor. of secs. 13, 18, 19, and 24, bears N. 1° 35' W., 77.64 chs. distant, monumented with the original sandstone, 14 x 12 x 8 ins. loosely set, on top of the ground, mkd. X on top, alongside of which is set a 3/4 in. T iron, firmly set, projecting 8 ins. above ground; from which the remaining original bearing tree:

- A fir, 50 ins. diam., bears N. 12 1/2° E., 76 lks. dist., with scribe marks S R9W visible on partially open blaze. (Record, N. 10°E.)

and bearing trees by Todd in 1894

- A root hole, bears S. 12° E., 66 lks. dist., with a down fir alongside, 22 ins. diam., with fragmentary scribe marks visible on partially open blaze.
- A fir, 26 ins. diam., bears S. 30° W., 40 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S	
R 10 W	R 9 W
S 13	S 18
S 24	S 19
1970	

from which new bearing trees

- A fir, 14 ins. diam., bears S. 69° E., 41 lks. dist., mkd. T22S R9W S19 BT.
 - A fir, 15 ins. diam., bears N. 67 1/2° W., 29 lks. dist., mkd. T22S R10W S13 BT.
- Deposit the original stone, and reset the T iron alongside the iron post.

Land, mountainous.
 Soil, rocky clay loam.
 Timber, fir, hemlock, cedar, oak, maple, yew, and dogwood;
 undergrowth, salal, hazel, Oregongrape, vine maple,
 poison oak, and fern.