

County Surveyor's Record, Douglas County, Oregon

14815

Dependent Resurvey, Portion of Subdivisional Lines, T. 22 S., R. 10 W.

CHAINS

77.35 Top of ascent, slopes E.; desc. 30 ft. over NE slope.

79.58 The cor. of secs. 25, 26, 35, and 36, occupied with the remains of the original corner tree, a fir snag, 40 ins. diam., with fragmentary scribe marks visible on partially open blaze on SE., with healed blazes on the NE., SW., and NW. faces, from which the remaining original bearing trees:

A sawed fir stump, 32 ins. diam., bears S. 61° W., 82 lks. dist., with healed blaze. (Record, S. 68° W.)

A sawed maple stump, 54 ins. diam., bears N. 38° W., 121 lks. dist., with healed blaze. (Record, N. 30° W.)

from which reference monuments and bearing objects

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 26 1/2° E., 15 lks. dist., with brass cap mkd. T22S R10W S25 RM 1970 and an arrow pointing to the corner.

A sandstone boulder, 30 x 20 x 15 ft. high, bears S. 35 1/4° E., 166 lks. dist. mkd. X B O, on N. face,

A sandstone boulder, 6 x 5 x 5 ft. high, bears S. 11 3/4° W., 54 lks. dist., mkd. X B O

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 57 1/4° W., 16 1/2 lks. dist., with brass cap mkd. T22S R10W S26 RM 1970 and an arrow pointing to the corner.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, oak, maple, madrone, and dogwood; undergrowth, salal, hazel, poison oak, Oregon grape, and fern.

From the 1/4 sec. cor. of secs. 25 and 36, determined at record distance from the original bearing trees:

A fir, 64 ins. diam., bears N. 76° E., 27 lks. dist., with scribe marks 1/4 S BT visible on bark blaze. (record, S. 15° E.,)

A fir, 38 ins. diam., bears S. 66 1/2° E., 56 lks. dist., with scribe marks 1/4 S BT visible on bark blaze. (Record, S. 20° W.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins in the ground, to bedrock, mkd. X, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

1/4 $\frac{S\ 25}{S\ 36}$
T 22 S R 10 W

from which a bearing object

Determined by Fritz Ingram's 1992 GIS Computations, not to be a corner point. Actually is the 1/4 corner for 25 only. (Note added 1-25-99 J.C.D.)

SEE ALSO M 93-14