

County Surveyor's Record, Douglas County, Oregon

14847

Dependent Resurvey, Portion of Subdivisional Lines, T. 22 S., R. 10 W.

CHAINS	
	<p>A hemlock, 20 ins. diam., bears N. 68° E., 205 lks. dist., mkd. S 1/16 S25 BT.</p> <p>A fir, 8 ins. diam., bears N. 83° W., 64 lks. dist., mkd. S 1/16 S26 BT.</p> <p>Ascend 160 ft. over SW. slope.</p>
21.00	Same dirt road, 10 lks. wide, bears E. and W.
30.70	Spur, slopes S. 70° W.; desc. 315 ft. over broken N. slope.
38.86	Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in drill hole, in solid rock, with top mkd.</p> <div style="text-align: center;"> $\begin{array}{c} 1/4 \\ S\ 26 \mid S\ 25 \\ T\ 22\ S \mid R\ 10\ W \\ 1970 \end{array}$ </div> <p>from which</p> <p>A fir, 14 ins. diam., bears S. 40° E., 17 lks. dist., mkd. 1/4 S25 BT.</p> <p>A yew, 8 ins. diam., bears S. 71° W., 17 lks. dist., mkd. 1/4 S26 BT.</p> <p>Descend 380 ft. over NE. slope.</p>
46.65	Ravine, drains N. 60° W.; asc. 70 ft. over SW. slope.
49.15	Spur, slopes W.; desc. 80 ft. over NW. slope.
51.65	Ravine, drains S. 45° W.; asc. 275 ft. over S. slope.
58.29	Point for the N 1/16 sec. cor. of secs. 25 and 26
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} N\ 1/16 \\ S\ 26 \mid S\ 25 \\ 1970 \end{array}$ </div> <p>from which</p> <p>A fir, 16 ins. diam., bears N. 46° E., 10 lks. dist. mkd. N 1/16 S25 BT.</p> <p>A fir, 22 ins. diam., bears S. 51 1/2° W. 8 1/2 lks. dist., mkd. N 1/16 S26 BT.</p> <p>Ascend 625 ft. over S. slope.</p>
72.00	Spur ridge, bears E. and W.; desc. 120 ft. over precipitous N. slope.
75.00	Bottom of descent, slopes NW.; asc. 45 ft. over SW. slope.
77.72	The cor. of secs. 23, 24, 25, and 26, perpetuated and recorded by the Oregon State Board of Forestry, in 1962, monumented with a mound of stone, 3 ft. base,