

County Surveyor's Record, Douglas County, Oregon

14854

T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of a dependent resurvey of a portion of the subdivisional lines, T. 24 S., R. 4 W., Willamette Meridian, Oregon.

The history of surveys in that portion of the township pertaining to this resurvey is as follows:

The south boundary of the township and a portion of the subdivisional lines were surveyed by Harvey Gordon and Charles T. Gardner in 1855.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming closures were chained twice. Only those lines bounding or crossing public lands were blazed.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying instructions, 1947, and the Special Instructions, dated August 7, 1972, for Group 793, Oregon.

The directions of the lines were determined by deflection angles from azimuths obtained from direct solar observations.

The geographic position of the southeast corner of section 34, as scaled from the Glide, Oregon, quadrangle map, prepared by the United States Geological Survey, in 1954, is as follows:

Latitude 43° 26.0' N. Longitude 123° 08.9' W.

The mean magnetic declination is 19° 30' E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 24 S., R. 4 W., Willamette Meridian, Oregon

(Restoring the 1855 survey by Harvey Gordon and Charles T. Gardner, U. S. Deputy Surveyors)

Beginning at the corner of secs. 2, 3, 34, and 35, on the south boundary of the Tp., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
 T 24 S R
 S 34 | S 35 4
 S 3 | S 2 W
 T 25 S
 1963

from which the remaining original bearing trees

A white oak, 26 ins. diam., bears N. 5° E.,
 465 lks. dist., with partial scribe marks
 visible on opened blaze.

A white oak, 23 ins. diam., bears S. 10° E.,