

County Surveyor's Record, Douglas County, Oregon

~~14854~~

14855

Dependent Resurvey, Portion of subdivisional Lines,
T. 24 S., R. 4 W.- Willamette Meridian, Oregon

CHAINS

650 lks. dist., with partial scribe marks visible on opened blaze.

A white oak, 22 ins. diam., bears S. 7 1/4° W., 338 lks. dist., with partial scribe marks visible on opened blaze.

and bearing trees marked by Godfrey

A white oak, 18 ins. diam., bears S. 50° E., 96 lks. dist., with healed blaze.

A fir, 28 ins. diam., bears S. 75° W., 100 lks. dist., with healed blaze.

An incense cedar, 43 ins. diam., bears N. 51° W., 46 lks. dist., with healed blaze.

No suitable trees available within limits in the NE. quadrant.

N. 0° 07' W., bet. secs. 34 and 35, marking and blazing the true line.

Ascend 130 ft. over NW. slope through light timber and dense undergrowth, along barbed wire fence extending N. and S.

5.55 Spur, slopes N. 80° W.; desc. 220 ft. over NW. slope.

9.00 Same barbed wire fence, bears generally N. and S.

20.05 Point for the S 1/16 sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

S 1/16
S 34 | S 35
1972

from which

A fir, 18 ins. diam., bears N. 76 1/2° E., 141 lks. dist., mkd. S 1/16 S35 BT.

A fir, 13 ins. diam., bears N. 14° W., 6 lks. dist., mkd. S 1/16 S34 BT.

Descend 325 ft. over NW. slope.

40.10 Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 24 S R 4 W
1/4
S 34 | S 35
1972

FD. OF 12/95
BY CHRISTENSEN
M 123-21

from which

A fir, 27 ins. diam., bears S. 59° E., 71 1/2 lks. dist., mkd. 1/4 S35 BT.

A fir, 6 ins. diam., bears N. 85° W.,