

# County Surveyor's Record, Douglas County, Oregon

14855

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

42 1/2 lks. dist., mkd. 1/4 S34 BT.

Descend 20 ft. over NW. slope.

40.80 Creek, 1 lk. wide, course N. 70° W.; asc. 200 ft. over SW slope.

44.00 Barbed wire fence, bears N. 70° W., and S. 70° E.

53.85 Spur, slopes W.; desc. 145 ft. over NW. slope.

60.15 Point for the N 1/16 sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16  
S 34 | S 35  
1972

from which

A fir, 17 ins. diam., bears N. 49 1/2° E.,  
32 lks. dist., mkd. N. 1/16 S35 BT.

A fir, 17 ins. diam., bears S. 7 1/2° W.,  
53 lks. dist., mkd. N. 1/16 S34 BT.

Descend 120 ft. over NW. slope.

65.95 Leave timber, enter open bottom land, edge bears NE. and SW.; also leave barbed wire fence, bears generally NE., and S.

68.00 Long Valley Creek, 1 lk. wide, course S. 10° W.; asc. 45 ft over SE. slope.

80.20 Point for the cor. of secs. 26, 27, 34, and 35 at proportionate distance; there is no remaining evidence of the original corner.

*FD. OK 12/95  
BY CHRISTENSEN  
M 123-21*

T 24 S R 4 W  
S 27 | S 26  
S 34 | S 35  
1972

from which

A fir, 8 ins. diam., bears N. 75° E.,  
479 lks. dist., mkd. T24S R4W S26 BT.

A fir, 15 ins. diam., bears S. 44 3/4° E.,  
369 lks. dist., mkd. T24S R4W S35 BT.

A fir, 13 ins. diam., bears S. 17° W.,  
319 lks. dist., mkd. T24S R4W S34 BT.

A fir, 35 ins. diam., bears N. 15° W.,  
133 lks. dist., mkd. T24S R4W S27 BT.

Land, mountainous.  
Soil, rocky clay loam.  
Timber, fir, hemlock, alder, madrone, cedar, dogwood, white oak, black oak, and maple; undergrowth, salal, hazel, fern, poison oak, and vine maple