

County Surveyor's Record, Douglas County, Oregon

14857

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridain, Oregon

CHAINS

From the 1/4 sec. cor. of secs. 26 and 35, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S

1/4 $\frac{S\ 26}{S\ 35}$

R 4 W

1963

from which the remains of an original bearing tree

A root hole, bears S 58° W., 36 lks. dist., with a down and rotted oak alongside, size indeterminate, no marks visible on opened blaze.

and bearing trees marked by Godfrey

A fir, 17 ins. diam., bears S. 33° W., 18 lks. dist., with healed blaze.

A fir, 13 ins. diam., bears N. 12° W., 27 lks. dist., with healed blaze.

S. 89° 09' W., bet. secs. 26 and 35.

Ascend 15 ft. over SW. slope through moderate timber and dense undergrowth.

4.50 Top of ascent, slopes SW.; desc. 310 ft. over NW. slope.

19.855 Point for the W 1/16 sec. cor. of secs. 26 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 26}{S\ 35}$
1972

from which

A fir, 8 ins. diam., bears N. 32° E., 58 lks. dist., mkd. W 1/16 S26 BT.

A fir, 17 ins. diam., bears S. 12° E., 20 lks. dist., mkd. W 1/16 S35 BT.

Descend 10 ft. over SW. slope

25.50 Ravine, drains S. 70° W.; asc. 60 ft. over SE. slope.

26.50 Spur, slopes S. 30° W.; desc. 180 ft. over NW. slope

35.00 Barbed wire fence, bears N. and S.; also leave timber, edge bears N. and S.

37.30 Long Valley Creek, 1 lk. wide, course S.; asc. 30 ft. over SE. slope.

39.71 The cor. of secs. 26, 27, 34, and 35.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, alder, madrone, white oak, black oak,