

County Surveyor's Record, Douglas County, Oregon

14861

T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of that portion of township 26 south, range 7 west, pertaining to this resurvey, is as follows:

The west boundary was surveyed by Dennis Hathorn, in 1855, the west boundary was resurveyed and subdivisional lines were surveyed by Addison R. and Samuel C. Flint, in 1881.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines were chained twice. Only those lines bounding, or crossing public lands were blazed.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated June 24, 1969, under Group No. 696, Oregon.

The directions of the lines were determined by the Solar Transit method, and from azimuths obtained from direct solar observations.

The geographic position of the 1/4 section corner of sections 17 and 20, as scaled from the Tyee, Oregon, quadrangel map, published by the United States Geological Survey, in 1955, is as follows:

Latitude 43° 18.1' N. Longitude 123° 33.1' W.

The mean magnetic declination is 19° 15' E.

Dependent Resurvey of a portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the 1881 survey by Addison R. and
Samuel C. Flint, U. S. Deputy Surveyors)

Beginning at the 1/4 sec. cor. of secs. 19 and 20, determined at record distance from the remaining original bearing trees:

A sawed fir stump, 60 ins. diam., bears S. 69° E., 50 lks. dist., no marks remaining on burned blaze. (Record, S. 80° E.)

A sawed fir stump, 48 ins. diam., bears N. 23° W., 32 lks. dist.; no marks remaining on burned blaze. (Record, N. 35° W.)

At the corner point

Set an ironpost, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.