

County Surveyor's Record, Douglas County, Oregon

14862

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S., R. 7 W.

CHAINS

T 26 S R 7 W
1/4
S 19 | S 20
1969

from which new bearing trees

A fir, 3 ins. diam., bears N. 49° E., 29 1/2 lks. dist., mkd. X BT.

A fir, 5 ins. diam., bears N. 55° W., 43 lks. dist., mkd. 1/4 S19 BT.

N. 0° 12' E., bet. secs. 19 and 20 marking and blazing the true line.

Descend 40 ft. over NE. slope through light timber and dense undergrowth.

- 2.20 Hubbard Creek, 20 lks. wide, course N. 60° W., asc. 405 ft. over SW. slope.
- 3.25 Hubbard Creek Road, 30 lks. wide, bears N. 60° W. and S. 60° E.
- 11.00 Small rock bluff, 20 lks. high, faces S., continue ascent over SW. slope.
- 19.05 Spur, slopes S. 45° W.; asc. 35 ft. over SW. slope.
- 20.85 Dry creek bed, 2 lks. wide, drains S. 70° W.; asc. 190 ft. over SW. slope.
- 31.50 Dirt road, 20 lks. wide, bears E. and W.
- 32.15 Dirt road, 20 lks. wide, bears N. 70° E. and S. 70° W.
- 33.30 Spur ridge, bears N. 70° E. and S. 70° W.; desc. 115 ft. over N. slope.
- 39.94 Point for the cor. of secs. 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mdk.

T 26 S R 7 W
S 18 | S 17
S 19 | S 20
1969

from which

A fir, 5 ins. diam., bears N. 17 3/4° E., 71 lks. dist., mkd. T26S R7W S17 BT.

A fir, 5 ins. diam., bears S. 16° E., 28 lks. dist., mkd. T26S R7W S20 BT.

A fir, 5 ins. diam., bears S. 72 1/2° W., 39 1/2 lks. dist., mkd. T26S R7W S19 BT.

A fir, 5 ins. diam., bears N. 52° W., 37 lks. dist., mkd. T26S R7W S18 BT.

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, cedar, tan oak, maple, myrtle,