

County Surveyor's Record, Douglas County, Oregon

14864

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S., R. 7 W.

CHAINS

from which

A fir, 11 ins. diam., bears N. 38° W., 27 lks. dist., mkd. E 1/16 S18 BT.

A fir, 35 ins. diam., bears S. 75° W., 53 1/2 lks. dist., mkd. E 1/16 S19 BT.

Descend 120 ft. over W. slope.

31.65 Dirt road, 15 lks. wide, bears N. 10° E. and S. 10° W.

40.21 Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.

Set an ironpost, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 7 W
 $\frac{1}{4} \frac{S 18}{S 19}$
 1969

from which

A fir, 6 ins. diam., bears N. ~~1/16 1/2~~^{N. 16 1/2 W}° W., 11 1/2 lks. dist. mkd. 1/4 S18 BT.

A fir, 5 ins. diam., bears S. 23 1/2° E., 20 1/2 lks. dist. mkd. 1/4 S19 BT.

Descend 55 ft. over W. slope.

45.40 Dry creek bed, 2 lks. wide, drains S. 60° E.; desc. 450 ft. over broken W. slope.

77.90 Hubbard Creek, 20 lks. wide, course N.; asc. 20 ft. over E. slope.

80.05 Junction of dirt road, 15 lks. wide, with Hubbard Creek Road, 20 lks. wide, bears North and S. 15° E., and S. 10° W.

80.70 The cor. of secs. 13, 18, 19, and 24, on the west bdy. of the Tp., perpetuated and recorded by Richard C. Grant, Registered Engineer No. 2807, in 1958, from testimony of longtime local residents, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

$\frac{S 13}{S 24} \frac{S 18}{S 19}$
 1969
 T 26 S R 7 W

from which new bearing trees

A fir, 4 ins. diam., bears N. 81 1/2° E., 36 lks. dist., mkd. X BT.

A fir, 6 ins. diam., bears S. 86 1/2° E., 200 lks. dist., mkd. T26S R7W S19 BT.

A fir, 4 ins. diam., bears S. 11° W., 8 1/2 lks. dist., mkd. X BT.