

County Surveyor's Record, Douglas County, Oregon

14868

T. 26 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 26 south, range 8 west, Willamette Meridian, Oregon.

The history of surveys in that portion of the township covered by this resurvey is as follows:

The subdivisional lines were surveyed by William P. Heydon, in 1896.

A portion of the subdivisional lines was resurveyed and sections 30 and 32 were subdivided by Peter A. Peterson, in 1967.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only lines bounding, or crossing Federal public lands were blazed.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947, and Special Instruction, dated February 29, 1972, for Group No. 763, Oregon.

The directions of the lines were determined by deflection angles from azimuths obtained by direct solar observations.

The geographic position of the corner of sections 20, 21, 28, and 29, as scaled from the Tye, Oregon, quadrangle map, prepared by the United States Geological Survey, in 1955, is as follows:

Latitude $43^{\circ} 17.2' N.$ Longitude $123^{\circ} 39.8' W.$

The mean magnetic declination is $19^{\circ} 24' E.$

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 8 W., Willamette Meridian, Oregon.

(Restoring the 1896 survey by William P. Heydon, U.S. Deputy Surveyor)

From the corner of secs. 20, 21, 28, and 29, perpetuated and recorded by Marvin C. Ramsey, RLS. No. 404, in 1957, from which the remaining original bearing object:

A basalt boulder 8 ft. x 6 ft. x 4 ft., above ground, bears N. $60^{\circ} E.$, 40 lks. dist., mkd. X on W. face.

and trees marked by Ramsey

A root hole, bears N. $67 \frac{1}{2}^{\circ} E.$, 59 lks. dist., with a down fir alongside, 14 ins. diam., with illegible scribe marks on root blaze.

A cedar snag, 8 ins. diam., bears S. $82 \frac{1}{2}^{\circ} E.$, 48 lks. dist., with scribe marks T26S R8W S28 RS 404 BT visible on open blaze.