

# County Surveyor's Record, Douglas County, Oregon

14869

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S., R 8 W.

Willamette Meridian, Oregon

CHAINS

A hemlock, 8 ins. diam., bears S. 42 1/2° W.,  
42 lks. dist., with scribe marks T26S R8W  
S 29 RS 404 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long 2 1/2 ins. diam., 20 ins. in the  
ground, and in a mound of stone, 36 in. base, to top, with brass  
cap mkd.

T 26 S R 8 W  
S 20 | S 21  
S 29 | S 28  
1972

from which new bearing objects

A basalt boulder, 4 ft. x 3 ft. x 2 ft., bears  
S. 50° E., 85 lks. dist., mkd. XBO on NW face.

A basalt boulder, 6 ft. x 4 ft. x 4 ft., bears  
N. 53° W., 44 1/2 lks. dist., mkd. XBO on SE face.

No suitable trees available within limits.

Set a 5 ft. steel fence post alongside iron post.

N. 0° 39' W., bet. secs. 20 and 21, marking and blazing the true  
line.

Descend 17 ft. along creek bottom coursing NW., through heavy  
timber and moderate undergrowth.

2.70 Creek, 15 lks. wide, course NW., asc. 112 over SW. slope.

10.05 Top of ascent, slopes W., desc. 5 ft. over NW slope.

11.20 Creek, 3 lks. wide, course S. 65° W.; asc. 245 ft. over W. slope.

19.10 Spur, slopes W.; desc. 393 ft. over NW slope.

32.50 Creek, 4 lks. wide, course N. 55° W.; asc. 26 ft. over SW. slope.

34.15 Spur, slopes W.; desc. 72 ft. over NW. slope.

38.86 Point for the 1/4 sec. corner of secs. 20 and 21, at proportionate  
distance; there is no remaining evidence of the original corner.

Set an iron post, 28 inches long, 2 1/2 inches diameter, 24 inches  
in the ground, with brass cap marked.

T 26 S R 8 W  
1/4  
S 20 | S 21  
1972

from which

A hemlock, 13 ins. diam., bears S. 72° E.,  
77 lks. dist., mkd. 1/4 S21 BT.

A hemlock, 11 ins. diam., bears S. 10° W.,  
67 lks. dist., mkd. 1/4 S20 BT.

Descend 4 ft. over NW. slope.