County Surveyor's Record, Douglas County, Oregon

14870

Dependent Resurvey, Portion of Subdivisional Lines. T. 26 S., R 8 W. Willamette Meridian, Oregon

CHAINS	
40.30	Creek, 50 lks. wide, course N. 20° W.; asc. 35 ft. over SW. Slope.
42.20	Rocky spur, slopes S. 60° W.; desc. 51 ft. along W. slope.
49.55	Same creek, 45 lks. wide, course N. 40° E.; asc. 20 ft. over SE slope.
52.30	Spur, slopes N. 75° E.; desc. 16 ft. over NE. slope.
54.50	Creek, 10 lks. wide, course N. 65° E.; asc. 141 ft. over SE slope.
63.70	Spur, slopes E.; desc. 42 ft. over NE slope.
65.45	Creek, 5 lks. wide course S. 65° E.; asc. 104 ft. over SE. slope.
69.20	Spur, slopes E.; desc. 73 ft. along E. slope.
77.72	The corner of secs. 16, 17, 20, and 21, perpetuated and recorded by Weyerhauser Timber Company, in 1968, monumented with a cedar post, 3 ins. diam., firmly set, protruding 18 ins. above the ground, from which the remaining original bearing trees: A fir, 45 ins. diam., bears S. 10° W., 130 lks. dist., with scribe marks S20 T26S R8W BT visible on bark blaze, (Record and to face, 125 lks.) A hemlock, 21 ins. diam., bears N. 60° W., 7 lks. dist., with partial scribe marks visible on open blaze. and trees marked by Weyerhauser in 1968 A hemlock, 11 ins. diam., bears N. 41° E., 12 lks. dist., with scribe marks T. 26S R8W S16 BT visible on opened blaze, and a galvanized nail with "W" embossed on head driven in base of tree. * [illegible] At the corner point Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T 26 S R 8 W S 17 | S 16 S 20 | S 21 1972 Land, mountainous. Soil, rock clay, humus. Timber, fir, hemlock, cedar, alder, maple, chinquapin; undergrowth, vine maple, sword fern, huckleberry, salal, manzanita, and rhododendron.

From the corner of secs. 20, 21, 28, and 29.

* A fir, 22 ins. diam., bears S. 7 1/4° E., 22 lks. dist., with scribe marks T26S R8W S21 BT visible on opened blaze, and a galvanized nail with "W" embossed on head driven in base of tree.