

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S., R. 8 W.

14871

Willamette Meridian, Oregon

CHAINS

S. 88° 45' W. bet. secs. 20 and 29.

Descend 4 ft. over W. slope, through heavy timber and moderate undergrowth.

.30 Creek 15 lks. wide, course N. 15° W.; asc. 526 ft. over N.E. slope.

15.15 Spur, slopes NE.; desc. 84 ft. over NW. slope.

17.75 Ravine, drains. N.; asc. 119 ft. over NE. slope.

24.15 Spur, slopes N.; desc. 500 ft. over NW. slope.

36.25 Creek, 15 lks. wide, course N.; asc. 255 ft. over SE. slope.

40.40 Point for the 1/4 section corner of sections 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 inches long, 2 1/2 inches diameter, 24 inches in the ground, with brass cap marked.

T 26 S R 8 W
1/4 $\frac{S 20}{S 29}$
1972

from which

A fir, 33 inches diameter, bears N. 43° E., 82 links distance, marked 1/4 S20 BT.

A hemlock, 13 inches diameter, bears S. 61 1/2° E., 54 1/2 links distance, marked 1/4 S29 BT.

Set a 5 ft. steel fence post alongside iron post.

Ascend 247 ft. over SE. slope.

53.70 Spur, slopes S. 10° W.; desc. 49 ft. over SW. slope.

58.40 Ravine, drains S.; asc. 96 ft. along S. slope.

70.65 Rock outcropping, faces S.; desc. 39 ft. over SW. slope.

71.70 Ravine, drains S.; asc. 89 ft. along SE. slope.

78.15 Top of ascent, slopes S.; desc. 16 ft. along S. slope.

80.80 The corner of secs. 19, 20, 29, and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T 26 S R 8 W
S 19 | S 20
S 30 | S 29
1967

from which the remains of an original bearing tree:

A cedar snag, 25 ins. diam., bears S 52° W., 210 lks. dist., with fragmentary scribe marks visible on rotted and burned blaze.

and trees marked by Peterson, in 1967