

# County Surveyor's Record, Douglas County, Oregon

575-14873

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S. R.8 W.,

Willamette Meridian, Oregon

CHAINS

dist., mkd. 1/4 S20 BT

A fir, 13 ins. diam., bears N. 63° W., 38 lks.  
dist., mkd. 1/4 S19 BT.

Set a 5 ft. steel fence post alongside the  
iron post.

Descend 65 ft. over N. slope.

24.45 Creek, 2 lks. wide, course N. 80° E.; asc. 94 ft. over SE slope.

27.40 Dirt road 22 lks. wide, bears N. 80° E. and S. 80° W.

27.55 Edge of timber, bears N. and E.; continue along E. edge of timber.

27.70 Spur, slopes N. 50° E.; desc. 5 ft. over NE. slope.

29.59 An original line tree, a fir, 52 ins. in diam., mkd. with 3 notches  
on S. face.

This point now becomes an angle point in the line.

N. 0° 35' E., beginning a new measurement.

Descend 35 ft. over NE slope.

1.15 Ravine, drains N. 70° E.; asc. 22 ft. over SE slope.

3.60 Spur, slopes N. 65° E.; desc. 23 ft. over NE slope.

5.40 Ravine, drains N. 75° E.; asc. 8 ft. over SE slope.

7.55 Spur, slopes E.; desc. 155 ft. over NE. slope.

19.20 Creek, 5 lks. wide, course E.; asc. 168 ft. over S. slope.

24.35 Spur, slopes E.; desc. 72 ft. over N. slope.

24.60 Dirt road 20 lks. wide, bears S. 75° E. and W.

32.66 The corner of secs. 17, 18, 19, and 20, determined from the original  
bearing trees:

from which:

A hemlock, 23 ins. diam., bears N. 72° E.,  
50 lks. dist., with partial scribe marks  
visible on opened blaze. (Record, N. 68° E.)

A cedar, 20 ins. diam., bears S. 62° E.,  
22 lks. dist., with scribe marks 26 visible  
on opened blaze. (Record, 17 lks.)

A hemlock, 33 ins. diam., bears S. 72° W.,  
30 lks. dist., with partial scribe marks  
visible on opened blaze.

A hemlock, 25 ins. diam., bears N. 70 1/2° W.,  
18 lks. dist., with partial scribe marks  
visible on opened blaze. (Record, 22 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.