

County Surveyor's Record, Douglas County, Oregon

14874

Dependent Resurvey, Portion of Subdivisional Lines, T. 26 S., R. 8 W.

~~Willamette Meridian, Oregon~~

CHAINS

in the ground, with brass cap mkd.

T 26 S R 8 W
S 18 | S 17
S 19 | S 20
 1972

Land, mountainous.
 Soil, rocky-clay, loam.
 Timber, fir, hemlock, cedar, alder, chinquapin, maple;
 undergrowth, rhododendron, sword fern, vine maple,
 salal, manzanita, Oregon grape, and salmonberry.

From the cor. of secs. 16, 17, 20, and 21.

S. 89° 31' W., bet. secs. 17 and 20.

Ascend 573 ft. over E. slope through heavy timber and moderate undergrowth.

- 1.80 Top of rock bluff, 30 ft. high, edge bears E. and W.
- 3.90 Top of rock bluff, 50 ft. high, edge bears E. and W.
- 10.50 Spur, slopes N.; desc. 65 ft. over NW. slope.
- 14.40 Ravine, drains. N. 10° E.; asc. 222 ft. over E. slope.
- 24.80 Spur, slopes S. 40° E.; desc. 67 ft. over SW. slope.
- 27.80 Creek 2 lks. wide, course S. 20° E.; asc.; 205 ft. over SE slope.
- 40.48 The 1/4 sec. cor. of secs. 17 and 20, perpetuated and recorded by Arthur Boyer, Registered Engineer, No. 1581, in 1952, monumented with a wooden post, 6 ins. x 6 ins., loosely set, protruding 3 ft. above the ground, mkd. S20, S17 1/4 on N. face, from which the original bearing trees:
 - A fir snag, 53 ins. diam., bears N. 43° E., 65 lks. dist., with axe marks visible on rotted face.
 - A fir snag, 18 ins. diam., bears N. 40° W., 77 lks. dist., with scribe marks BT visible on rotted bark blaze.

and trees marked by Boyer in 1952.

- A fir, 25 ins. diam., bears N. 53 1/2° E., 6 lks. dist., with partial scribe marks visible on opened blaze.
- A fir, 16 ins. diam., bears S. 63° W., 13 lks. dist., with illegible scribe marks visible on partly healed blaze.
- A chinquapin, 22 ins. diam., bears N. 40° W., 74 lks. dist., with scribe marks S T visible on partly healed blaze.

At the corner point

Set on iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.