

County Surveyor's Record, Douglas County, Oregon

378

Dependent Resurvey, Portion of Subdivisional Lines, T. 31 S., R. 6 W.

CHAINS

A fir, 24 ins. diam., bears S. 6 1/2° E., 95 1/2 lks. dist., with scribe marks 1/4 S12 CS visible on partially opened blaze.

Refurbish the iron post with a collar of stones, 2 ft. base, to top.

No other trees available within limits.

N. 89° 01' W., bet. secs. 1 and 12, marking and blazing the true line.

Descend 380 ft. over NW. slope, through old logged area and dense undergrowth.

4.05 Gravel road, 15 lks. wide, bears N. 5° E. and S. 5° W.

15.70 Gravel road, 15 lks. wide, bears N. 30° W., and S. 30° E.

17.40 Ravine, drains S. 20° W.; asc. 30 ft. over SE. slope.

20.13 Point for the W 1/16 cor. of secs 1 and 12.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

W 1/16 S 1
 S 12
1969

from which

A fir, 30 ins. diam., bears N. 54 1/2° E., 129 lks. dist., mkd. W 1/16 S1 BT.

A fir, 30 ins. diam., bears S. 60 1/2° W., 256 lks. dist., mkd. W 1/16 S12 BT.

Ascend 20 ft. over steep cut bank.

20.33 Gravel road, 15 lks. wide, bears NE., curving E., and SW., curving W.

21.40 Spur, slopes S.; desc. 110 ft. over SW. slope.

23.00 Same gravel road, 15 lks. wide, bears N. 70° W., and S. 70° E.

27.25 Ravine, drains S.; asc. 55 ft. over SE. slope.

30.85 Spur, slopes S. 20° W.; desc. 35 ft. over SW. slope.

35.70 Spur, slopes S. 55° W.; 170 ft. over NW. slope.

40.26 The cor. of secs. 1, 2, 11, and 12, determined from the remains of the original bearing trees:

A sawed fir stump, 33 ins. diam., bears S. 10 1/4° E., 44 lks. dist., no marks visible. (Record, S. 24° E.)

A fir snag, 16 ins. diam., bears N. 66 3/4° W., 64 lks. dist., with axe marks visible on bark. (Record, N. 65° E., 59 lks. dist.)

and trees mkd. by George J. Wednroth, R.L.S. No. 5, in 1966