

County Surveyor's Record, Douglas County, Oregon

2880

Dependent Resurvey, Portion of Subdivisional Lines, T. 31 S., R. 6 W.

CHAINS	
	<p>from which</p> <p style="margin-left: 40px;">A madrone, 7 ins. diam., bears S. 86 1/2° E., 43 1/2 lks. dist., mkd. 1/4 S1 BT.</p> <p style="margin-left: 40px;">A madrone, 6 ins. diam., bears S. 56° W., 54 lks. dist., mkd. 1/4 S2 BT.</p> <p style="margin-left: 40px;">The corner is located on a steep hillside, slopes NE.; also edge of timber, bears NW. and SE.</p> <p>Descend 240 ft. over NE. slope.</p>
48.00	Slope changes to E.; desc. 130 ft.
59.85	<p>Point for the N 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>N 1/16</p> <p>S 2 S 1</p> <p>1969</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 37 ins. diam, bears N. 53° E., 24 lks. dist., mkd. N. 1/16 S1 BT.</p> <p style="margin-left: 40px;">A fir, 32 ins. diam, bears S. 41° W., 21 lks. dist., mkd. N 1/16 S2 BT.</p> <p>Descend 270 ft. along E. slope.</p>
61.20	Creek, 1 lk. wide, course E.; asc. 5 ft. over SE. slope.
63.40	Spur, slopes N. 70° E.; desc. 100 ft. over NE. slope.
67.60	Ravine, drains E.; asc. 10 ft. over SW. slope.
71.00	Spur, slopes N. 60° E.; desc. 220 ft. over NW. slope.
79.30	Junction of fences, extending N. and SE.; thence along meandering fence line.
80.70	Dry creek bed, 3 lks. wide, drains. N. 50° E.; asc. 5 ft. over SE. slope.
81.30	<p>The cor. of secs. 1, 2, 35, and 36, monumented with an iron pipe, 1 1/2 ins. diam., firmly set 6 ins. above the ground, alongside of which is another iron pipe, 1 ins. diam., firmly set 6 ins. above the ground, from which the remains of the original bearing trees:</p> <p style="margin-left: 40px;">A madrone, 40 ins. diam., bears S. 81 1/2° E., 37 lks. dist., with scribe mark S visible on opened blaze. (Record, S. 83° E., 34 lks. dist.)</p> <p style="margin-left: 40px;">A madrone, 18 ins. diam., bears S. 3 1/2° W., 81 lks. dist., with scribe marks S2 2880 BT, on bark. (Record, S. 5° W.)</p> <p style="margin-left: 40px;">A madrone, 27 ins. diam., bears N. 30 1/2° W., 55 lks. dist., with scribe marks S35 2880 BT on bark. (Record, N. 36° W., 41 lks. dist.)</p> <p>At the corner point</p>