

County Surveyor's Record, Douglas County, Oregon

2802
14883

T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of a dependent resurvey of a portion of the west bdy. and a portion of the subdivisional lines of township 30 south, range 7 west, Willamette Meridian, Oregon.

The history of surveys of that portion of township 30 south, range 7 west, Willamette Meridian, Oregon, included in the following resurvey, is as follows:

The west boundary and a portion of the subdivisional lines of the township were surveyed by William H. Byars, in 1882.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, the Special Instructions dated July 6, 1972, and the Supplemental Instructions dated July 12, 1972.

The directions of the lines were determined by deflection angles from azimuths obtained by direct solar observations.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original position; lost corners were reestablished and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the corner of secs. 20, 21, 28, and 29, as scaled from the Dutchman Butte, Oregon, quadrangle map, prepared by the United States Geological Survey, in 1946, is as follows:

Latitude $42^{\circ} 56.5' N$. Longitude $123^{\circ} 32.6' W$.

The mean magnetic declination is $19^{\circ} 39' E$.

Dependent Resurvey of a Portion of the West Bdy.,
T. 30 S., R. 7 W., Willamette Meridian, Oregon

(Reestablishment of the Survey executed by
William H. Byars, Deputy Surveyor, in 1882)

Beginning at the $1/4$ sec. cor. of sec. 25 and 30, on the W. bdy. of the Tp., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1964, monumented with an iron post, 2 ins. diam. firmly set, projecting 15 ins. above ground, with brass cap mkd.

	T 30 S	
R 1/4		R
8		7
W S 25		S 30 W
	1964	

from which the remains of the original bearing trees:

A fir snag, 18 ins. diam., bears S. $72^{\circ} E$.,
22 lks. dist., with scribe mark B visible
on opened blaze.

A fir, 32 ins. diam., bears N. $64^{\circ} W$., 22 lks.
dist., with healed blaze. This tree remarked