

# County Surveyor's Record, Douglas County, Oregon

**14884**

Dependent Resurvey of a Portion of the W. Bdy.,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS																					
	CS on bark blaze, by Byron in 1964.																				
	and trees mkd. by Byron, in 1964																				
	A fir, 16 ins. diam., bears S. 72° E., 61 lks. dist., no marks visible on pitched over blaze.																				
	N. 0° 06' W., bet secs. 25 and 30, marking and blazing the true line.																				
	Desc. 12 ft. over broken NW. slope through heavy timber and moderate undergrowth, along edge of timber, bears N. and S.																				
3.90	Ravine, drains. S. 60° W.; asc. 193 ft. over SW. slope.																				
6.90	Corner of timber; edge bears S. and W.																				
19.54	Point for the N 1/16 sec. cor. of secs. 25 and 30.																				
	Set an iron post, 28 ins. long, 2 1/2 ins. diam, 26 ins. in the ground, with brass cap mkd.																				
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 5px;">N</td><td style="padding: 0 5px;">1/16</td><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;">30</td></tr> <tr><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;">25</td><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;">30</td></tr> <tr><td colspan="4" style="text-align: center; padding: 0 5px;">1972</td></tr> </table>	N	1/16	S	30	S	25	S	30	1972											
N	1/16	S	30																		
S	25	S	30																		
1972																					
	from which																				
	A fir, 15 ins. diam., bears N. 41° E., 57 lks. dist., mkd. N 1/16 S30 BT.																				
	A fir, 20 ins. diam., bears N. 64 1/2° W., 78 lks. dist., mkd. N 1/16 S25 BT.																				
	Ascend 93 ft. over SW. slope.																				
23.85	Spur, slopes S. 70° W.; desc. 17 ft. over NW. slope.																				
25.50	Ravine, drains. S. 60° W.; asc. 271 ft. over SW. slope.																				
38.55	Rocky spur, slopes N. 80° W.; desc. 28 ft. over NW. slope.																				
39.08	Point for the cor. of secs. 19, 24, 25, and 30, at proportionate distance; there is no remaining evidence of the original corner.																				
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.																				
	<table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 0 5px;">T</td><td style="padding: 0 5px;">30</td><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;"></td></tr> <tr><td style="padding: 0 5px;">R</td><td style="padding: 0 5px;">8</td><td style="padding: 0 5px;">W</td><td style="padding: 0 5px;">R 7 W</td></tr> <tr><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;">24</td><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;">19</td></tr> <tr><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;">25</td><td style="padding: 0 5px;">S</td><td style="padding: 0 5px;">30</td></tr> <tr><td colspan="4" style="text-align: center; padding: 0 5px;">1972</td></tr> </table>	T	30	S		R	8	W	R 7 W	S	24	S	19	S	25	S	30	1972			
T	30	S																			
R	8	W	R 7 W																		
S	24	S	19																		
S	25	S	30																		
1972																					
	from which																				
	A hemlock, 13 ins. diam., bears N. 10 1/2° E., 22 lks. dist., mkd. T30S R7W S19 BT.																				
	A cedar, 5 ins. diam., bears S. 68° E., 54 1/2 lks. dist., mkd. X BT.																				
	A fir, 9 ins. diam., bears S. 61° W., 34 lks. dist., mkd. T30S R8W S25 BT.																				
	A fir, 18 ins. diam., bears N. 41° W., 31 lks. dist., mkd. T30S R8W S24 BT.																				