

# County Surveyor's Record, Douglas County, Oregon

14885

Dependent Resurvey of a Portion of the W. Bdy.,  
T. 30 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, hemlock, cedar, pine, madrone, chinquapin, and oak;  
undergrowth, poison oak, fern, rhododendron, huckleberry, hazel,  
and manzanita.

N. 0° 06' W. bet. secs. 19 and 24.

Descend 280 ft. over broken NW. slope, through moderate timber and  
undergrowth.

- 3.85 Enter old logging area; edge bears N. and W.
- 14.30 Bottom of descent, drains N. 70° W.; asc. 20 ft. over SW. slope.
- 16.45 Top of rock outcrop, bears SW. and NW.; desc. 419 ft. over NW. slope.
- 39.08 The original 1/4 sec. cor. of secs. 19 and 24 occupied with the  
remains of the original corner tree, now a fir snag, 55 ins. diam.,  
with scribe marks S 1/4 visible on W. face.

from which the remains of the original bearing trees:

A root hole, bears N. 48° E., 58 lks. dist.,  
with a fallen fir, 39 ins. diam., alongside,  
no marks visible.

A sawed fir stump, 24 ins. diam., bears N.,  
80° W., 36 lks. dist., no marks visible on  
rotted blaze.

from which a reference monument and new bearing tree

An iron post, 28 ins. long, 2 1/2 ins. diam., set  
24 ins. in the ground, for a reference monu-  
ment, bears N. 45° E., 20 lks. dist., with  
brass cap mkd. 1/4 S19 RM 1972 and an arrow  
pointing to the corner.

A fir, 5 ins. diam., bears N. 65° W., 100 lks.  
dist., mkd. X BT.

N. 0° 27' W., beginning new measurement.

Descend 776 ft. over NW. slope, across old logged area, through  
dense undergrowth.

- 15.00 Dirt road, 20 lks. wide bears N. 30° E. and S. 45° W.
- 16.35 Same dirt road, 20 lks. wide, bears N. 70° W. and S. 60° E.
- 35.75 Ravine, drains N. 50° W.; asc. 43 ft. over SW. slope.
- 39.40 The cor. of secs. 13, 18, 19, and 24, perpetuated and recorded  
by Howard W. Johnstone, Registered Land Surveyor No. 498, for  
Roseburg Lumber Co. in 1961. Monumented with an iron pipe, 1 1/4  
ins. diam., firmly set, protruding 18 ins. above the ground,  
alongside of which is the original basalt stone, 18 x 12 x 10 ins.,  
firmly set, 8 ins. in the ground, mkd. with 3 notches on N. edge  
and 3 notches on S. edge.

from which the remains of the original bearing trees: